

# Quarterly Progress Report January through March 2001

Jervis B. Webb Company of California 5030 Firestone Boulevard South Gate, California

30 April 2001

2001 HAY 23 P 1: 52

# Erler & Kalinowski, Inc.

Consulting Engineers and Scientists 3250 Ocean Park Blvd., Suite 385 Santa Monica, California 90405 (310) 314-8855 Fax: (310) 314-8860

# Quarterly Progress Report: January through March 2001 Jervis B. Webb Company of California 5030 Firestone Boulevard, South Gate, California

## **Table of Contents**

1.	INTROD	UCTION	1
2.	QUARTI	ERLY GROUNDWATER MONITORING	2
	2.1. M	easurements of Groundwater Elevation	2
	2.2. G	roundwater Sampling	2
	2.2.1.	Groundwater Sampling Procedures	2
	2.2.2.	Analytical Results for Groundwater Samples	3
	2.2.3.	Quality Assurance/Quality Control	3
3.	SOIL RE	MEDIATION	5
	3.1. De	escription of the Soil Vapor Extraction System	5
	3.1.1.	Soil Vapor Wells	5
	3.1.2.	Soil Vapor Extraction and Treatment System	6
	3.2. O	peration and Monitoring of the SVE System	6
	3.2.1.	System Operation	6
	3.2.2.	System Monitoring	6
	3.2.3.	Soil Vapor Field Monitoring	7
	3.2.4.	Estimated Removal of VOCs	7
	3.2.5.	SCAQMD Compliance Monitoring	7
4.	PLANNE	D ACTIVITIES FOR NEXT QUARTER	9
5.	SUMMA	RY	0
6.	REFERE	NCES AND PREVIOUS REPORTS	1

## Quarterly Progress Report: January through March 2001 Jervis B. Webb Company of California 5030 Firestone Boulevard, South Gate, California

### **Table of Contents**

## LIST OF TABLES

- 1 Groundwater Elevations in Monitoring Wells
- 2 Results of VOCs Detected in Groundwater Samples
- 3 Additional Analytical Results for Groundwater Samples
- 4a Soil Vapor Extraction Data: Blower Influent
- 4b Soil Vapor Extraction Data: SVE-1
- 4c Soil Vapor Extraction Data: SVE-2
- 4d Soil Vapor Extraction Data: SVE-3
- 4e Soil Vapor Extraction Data: SVE-D1
- 4f Soil Vapor Extraction Data: VMP-D1
- 4g Soil Vapor Extraction Data: VMP-D2
- 4h Soil Vapor Extraction Data: VMP-1
- 5 Field Data for Soil Vapor Monitoring Probes

## Quarterly Progress Report: January through March 2001 Jervis B. Webb Company of California 5030 Firestone Boulevard, South Gate, California

### **Table of Contents**

## LIST OF FIGURES

1

2 Groundwater Monitoring Well Locations

Site Location Map

- 3 Elevation of the Groundwater Table on 4 January 2001
- 4 Elevation of the Groundwater Table on 22 February 2001
- 5 Elevation of the Groundwater Table on 8 March 2001
- 6 Concentrations of TCE in Groundwater
- 7 Layout of the Soil Vapor Extraction System
- 8 Soil Vapor Extraction System Schematic
- 9a Concentrations of Total VOCs versus Time: Blower Influent
- 9b Concentrations of Total VOCs versus Time: SVE-1
- 9c Concentrations of Total VOCs versus Time: SVE-2
- 9d Concentrations of Total VOCs versus Time: SVE-3
- 9e Concentrations of Total VOCs versus Time: SVE-D1
- 9f Concentrations of Total VOCs versus Time: VMP-D1
- 9g Concentrations of Total VOCs versus Time: VMP-D2
- 9h Concentrations of Total VOCs versus Time: VMP-1

## LIST OF APPENDICES

- A Groundwater Purge and Water Quality Monitoring Forms for Groundwater Sampling
- B Laboratory Reports and Chain-of-Custody Forms for Groundwater Sampling

### 1. INTRODUCTION

Erler & Kalinowski, Inc. ("EKI") is pleased to present this *Quarterly Progress Report*, *January through March 2001* for the property located at 5030 Firestone Boulevard and 9301 Rayo Avenue in South Gate, California (collectively referred to as the "Site," see Figure 1). The work documented in this report was performed on behalf of the Jervis B. Webb Company of California ("Webb"). The property at 5030 Firestone Boulevard is owned by Webb and the adjacent property at 9301 Rayo Avenue is owned by Reliable Steel Building Products, Inc. ("Reliable Steel").

The principal objectives of the activities performed during this quarter were to (1) monitor the groundwater wells at the Site, and (2) continue operation of the soil vapor extraction ("SVE") system at the Site. The quarterly groundwater monitoring activities described herein were performed in accordance with the procedures described in *Project Tasks, Schedule, and Work Plan for Additional Groundwater Investigation and Quarterly Groundwater Monitoring at the Jervis B. Webb Company Property* by EKI, dated 29 September 1998. The SVE activities described herein were performed in accordance with the *Work Plan for Clarifier Removal and Soil Remediation by Soil Vapor Extraction* by EKI, dated 14 April 1999 ("SVE Work Plan"). The California Regional Water Quality Control Board, Los Angeles Region ("RWQCB") approved the SVE Work Plan, with two modifications, in its letter to Webb dated 18 May 1999.

## 2. QUARTERLY GROUNDWATER MONITORING

### 2.1. Measurements of Groundwater Elevation

The depth to groundwater in each of the five groundwater monitoring wells at the Site was measured on 4 January, 22 February, and 8 March 2001 (see Figure 2 for well locations). These data are provided in Table 1. The depth to the groundwater table beneath the Site is approximately 45 feet below ground surface ("ft bgs"). Contours representing the elevation of the groundwater table on 4 January, 22 February, and 8 March 2001 are shown on Figures 3, 4, and 5, respectively. As inferred from the contours shown on these figures, the primary direction of groundwater flow in the groundwater table aquifer beneath the Site appears to be toward the south-southeast.

### 2.2. Groundwater Sampling

Samples of groundwater were collected from each of the five groundwater monitoring wells at the Site on 8 March 2001. In addition, a duplicate sample of groundwater was collected from well MW-2. All samples of groundwater were submitted to Orange Coast Analytical, Inc. in Tustin, California, for analyses of volatile organic compounds ("VOCs") using United States Environmental Protection Agency ("EPA") Method 8260B, total arsenic using EPA Method 206.2, and California Code of Regulations ("CCR") metals, including hexavalent chromium, using EPA Methods 200.7, 218.4, and 245.1. The analytical results for VOCs and metals detected in groundwater samples collected during this monitoring event are summarized in Tables 2 and 3, respectively.

#### 2.2.1. Groundwater Sampling Procedures

Prior to sampling of groundwater, each well was purged of a minimum of three well-casing volumes of groundwater using a submersible, electric pump. Groundwater purging was performed by West Hazmat Drilling Corp. ("West Hazmat") of Anaheim, California and groundwater samples were collected by Drewelow Engineering, Inc. ("Drewelow") of Encinitas, California. All down-hole equipment was thoroughly steam cleaned before use at each well.

During purging of the monitoring wells on 8 March 2001, the temperature, pH, conductivity, and turbidity of the purged groundwater were recorded by Drewelow. The instruments used for monitoring the purged groundwater were calibrated prior to commencement of groundwater purging. For each groundwater monitoring well, the time, water quality parameters, and volume of purged groundwater were recorded on forms in the field (see Appendix A). Purging at each well continued until the variability of the monitored groundwater quality parameters stabilized to within approximately ten percent. Groundwater

quality parameters were generally stable after purging three casing volumes of water from each well. The final turbidity of the purged groundwater was generally low, i.e., between 0.76 and 3.75 nephelometric turbidity units (see Appendix A).

A groundwater sample was collected from each monitoring well using a disposable polyethylene bailer. A new bailer was used to collect the sample from each well. A sample label that included a unique sample identification number, the time, and the date when the sample was collected was attached to each sample container. Sample containers were sealed in zip-lock plastic bags and placed in a cooler with ice for temporary storage and transport to the analytical laboratory. Chain-of-Custody forms were initiated in the field and stored with the samples. Laboratory reports and Chain-of-Custody forms for groundwater samples are attached in Appendix B.

### 2.2.2. Analytical Results for Groundwater Samples

#### 2.2.2.1. Volatile Organic Compounds

Trichloroethene ("TCE"), cis-1,2-dichloroethene ("c-1,2-DCE"), 1,1-dichloroethene ("1,1-DCE"), and toluene were the only VOCs detected in the samples of groundwater collected at the Site on 8 March 2001 (see Table 2). The concentrations of TCE detected in the samples of groundwater collected at the Site are shown on Figure 6. Consistent with previous results, TCE was the chemical of concern detected with the greatest frequency (five of six samples) and at the highest concentration (23,000 micrograms per liter ("ug/L") in well MW-1). The concentrations of TCE (<0.5 to 23,000 ug/L), c-1,2-DCE (<0.5 to 260 ug/L), and 1,1-DCE (<0.5 ug/L to 55 ug/L) detected in samples of the groundwater collected at the Site during March 2001 were within the ranges of concentrations detected during previous monitoring at the Site (see Table 2). The only detection of toluene, at a concentration of 140 ug/L, was in the sample of groundwater collected from well MW-5. No VOCs were detected in the sample of groundwater collected from downgradient monitoring well MW-4.

#### 2.2.2.2. Metals

As requested by the RWQCB in its meeting with Webb on 8 February 2001, the samples of groundwater collected at the Site during March 2001 were analyzed for CCR metals. Arsenic (5.6 to 320 ug/L), barium (19 to 150 ug/L), molybdenum (<50 to 1,100 ug/L), and zinc (12 to 25 ug/L) were the only metals detected in the samples of groundwater collected at the Site on 8 March 2001 (see Table 3).

#### 2.2.3. Quality Assurance/Quality Control

Standard laboratory QA/QC procedures used for the project included analyses of matrix spikes, matrix spike duplicates, a quality control check spike sample, and a method blank. The percent recoveries of the matrix spike, matrix spike duplicate, and the quality control check spike sample were within acceptable ranges. No analytes were detected in the method

blank samples analyzed for this project. QA/QC results are provided with the laboratory reports in Appendix B.

A duplicate groundwater sample was collected from monitoring well MW-2 (see Tables 2 and 3). Two VOCs (TCE and c-1,2-DCE) and four metals (total arsenic, barium, molybdenum, and zinc) were detected in both of the samples of groundwater collected from well MW-2. The relative percentage differences ("RPDs") for these analytes ranged between zero and 16 percent. These RPDs indicate an acceptable range of sampling and analytical reproducibility.

An equipment rinsate blank also was collected and analyzed during the groundwater sampling event on 8 March 2001. Following the sampling of well MW-3 and steam cleaning of the purge pump, the equipment rinsate blank was collected by pouring water over the pump into sample containers. The rinse water was provided by West Hazmat from an offsite source. A sample of the rinse water also was submitted to the analytical laboratory for analysis. The equipment rinsate blank and the sample of rinse water were analyzed for VOCs using EPA Method 8260B.

Several VOCs were detected in both the equipment rinsate blank and the sample of rinse water. TCE (120 ug/L), c-1,2-DCE (5.4 ug/L), and bromoform (2.3 ug/L) were detected in the equipment rinsate blank, and TCE (0.7 ug/L), bromoform (2.9 ug/L), and chlorodibromomethane (1.2 ug/L) were detected in the sample of rinse water. Bromoform and chlorodibromomethane were not detected in any of the samples of groundwater collected from the monitoring wells at the Site. The concentrations of TCE and c-1,2-DCE detected in the equipment rinsate blank were more than 90 percent lower than the concentrations detected in the sample of groundwater collected from well MW-3. As none of the chemicals detected in the equipment rinsate blank were detected at concentrations more than one-tenth of those detected in the sample of groundwater collected from the well purged prior to the decontamination activities, it does not appear that the rinse water quality or equipment cleaning procedures significantly compromised the integrity of the groundwater samples.

### 3. SOIL REMEDIATION

## 3.1. Description of the Soil Vapor Extraction System

### 3.1.1. Soil Vapor Wells

Four soil vapor extraction wells and four soil vapor monitoring probes were installed at the Site during June 1999 (see Figure 7). The wells and probes were designed to allow for vapor extraction and monitoring in both the shallow and deep vadose zones at the Site. All of the wells were constructed using Schedule 40 PVC casing and screen. More detailed descriptions of well construction and subsurface conditions at the Site are contained in reports previously provided to the RWQCB (see EKI, 14 April 1999; EKI, 13 October 1999).

On 29 June 2000, two of the soil vapor monitoring probes (VMP-D1 and VMP-D2) were converted to extraction wells by connecting the probes to the soil vapor extraction system at the Site with two-inch diameter PVC pipe. These wells have been used as extraction wells during system operation since 6 July 2000. On 8 March 2001, vapor monitoring probe VMP-1 was converted to an extraction well by connecting the probe to the soil vapor extraction system at the Site with a two-inch diameter hose. This well has been used as an extraction well during system operation since 8 March 2001.

Soil Vapor Extraction Wells: The four shallow vadose zone SVE wells (see locations SVE-1, SVE-2, SVE-3, and VMP-1 on Figure 7) are constructed with two-inch diameter PVC casing. Wells SVE-1, SVE-3, and VMP-1 have slotted screen from approximately 19 to 25 ft bgs, and have total depths of approximately 25 ft bgs. Well SVE-2 has slotted screen from approximately 18 to 24 ft bgs, and has a total depth of approximately 24 ft bgs.

The three deep vadose zone SVE wells are wells SVE-D1, VMP-D1, and VMP-D2. Well SVE-D1 is constructed with four-inch diameter PVC casing with slotted screen from approximately 30 to 40 ft bgs, and has a total depth of approximately 44 ft bgs. Deep vadose zone SVE wells VMP-D1 and VMP-D2 are constructed in the same boreholes with shallow vadose zone SVE wells SVE-2 and SVE-3, respectively, and are constructed with 2-inch diameter PVC casing. Well VMP-D1 has slotted screen from approximately 30 to 40 ft bgs, and has a total depth of approximately 43 ft bgs. Well VMP-D2 has slotted screen from approximately 31 to 41 ft bgs, and has a total depth of approximately 44 ft bgs.

Soil Vapor Monitoring Probes: The shallow vadose zone vapor monitoring probe (see location VMP-2 on Figure 7) is constructed with two-inch diameter PVC casing with slotted screen from approximately 19 to 25 ft bgs, and has a total depth of approximately 25 ft bgs.

### 3.1.2. Soil Vapor Extraction and Treatment System

Installation of the SVE system was completed at the Site during March 2000. Soil vapors from the extraction wells are passed through a condensate knock-out vessel and through a 200 cubic feet per minute ("cfm") blower (see Figure 8). The soil vapors are then passed through a heat exchanger and two 1,000-pound granular activated carbon ("GAC") vessels in series, with the treated vapors exhausted to the atmosphere under permit of the South Coast Air Quality Management District ("SCAQMD"). Valves on piping from each well and an ambient air inlet valve located ahead of the knockout vessel allow regulation of air extracted from the wells. PVC pipe and fittings are used throughout the system. Electrical power to the system is metered, and the system is enclosed in a fenced area.

Vacuum gauges, a hand-held flow meter, and sampling ports are used to monitor each of the vapor extraction wells. Vacuum is measured in inches of water column ("in-wc"), vapor flow rate is measured in actual cubic feet per minute ("acfm"), and concentrations of VOCs are measured in parts per million by volume ("ppmv"). Sampling ports were installed at each of the vapor wells and probes and several locations in the SVE system for monitoring of VOC concentrations.

### 3.2. Operation and Monitoring of the SVE System

### 3.2.1. System Operation

The SVE system began operating on 16 March 2000. Throughout this reporting period (i.e., January through March 2001), wells SVE-1, SVE-2, SVE-3, SVE-D1, VMP-D1, and VMP-D2 were used as vapor extraction wells. Well VMP-1 has been used as an extraction well since 8 March 2001. Operation and maintenance of the SVE system is performed by Drewelow.

The SVE system was shut down on 4 January 2001 following a static vapor sampling event (see EKI, 5 February 2001). The system was restarted on 19 February 2001 and was in operation through the remainder of the reporting period.

#### 3.2.2. System Monitoring

The following parameters have been monitored during operation of the SVE system: vapor flow rate from the extraction wells; total vapor flow rate; vacuum (pressure) at the extraction wells and monitoring points; blower influent flow rate and vacuum; blower discharge flow rate, pressure, and temperature; and VOC concentrations in the extracted soil vapor. The water level in the knockout tank is also monitored. No water had been observed in the knockout tank prior to a system shutdown on 21 June 2000. However, during this reporting period, water was observed in the piping of extraction well SVE-2 and the inlet manifold to the system blower. Approximately 200 gallons of water were removed from the SVE system

during this reporting period. The water is stored in 55-gallon drums and transported offsite for disposal and/or treatment.

Monitoring data collected at the inlet to the system blower prior to dilution with ambient air are presented in Table 4a and Figure 9a. Monitoring data collected at individual soil vapor extraction wells are presented in Tables 4b through 4h and Figures 9b through 9h. Field monitoring data for the soil vapor monitoring probes are presented in Table 5.

On 29 March 2001, flow rates in the four shallow zone extraction wells (SVE-1, SVE-2, SVE-3, and VMP-1) ranged from 2.3 to 2.7 acfm. The flow rates in the three deep zone extraction wells (SVE-D1, VMP-D1, and VMP-D2) ranged from 19 to 21 acfm at the end of the reporting period.

### 3.2.3. Soil Vapor Field Monitoring

Total VOC concentrations in soil vapor samples were also periodically monitored with an organic vapor meter, which utilizes a photoionization detector ("PID") to measure total concentrations of VOCs. The PID does not distinguish between individual compounds, but measures the total concentration of VOCs in samples of vapor. Samples of soil vapor were collected in Tedlar bags for the PID analyses. The PID was calibrated with 100 ppmv of isobutylene. PID readings from soil vapor samples collected at the system blower, the extraction wells, and the vapor monitoring probes are presented in Tables 4a through 4h and in Table 5. These data are plotted as a function of time on Figures 9a through 9h. The PID readings suggest that total VOC concentrations in the blower influent and each of the vapor wells decreased during this reporting period.

#### 3.2.4. Estimated Removal of VOCs

As no samples of soil vapor were collected for laboratory analysis during this reporting period, no estimates of VOC mass removal by the SVE system have been attempted for this reporting period. Based on measurements made at the blower influent and laboratory analytical data, it was estimated that a total of 133 pounds of VOCs, including 108 pounds of TCE, had been extracted from soil at the Site as of 14 December 2000 (see Table 4a and EKI, 5 February 2001). Given that the PID readings for vapor samples collected from the SVE system during this reporting period were generally lower than previous measurements, it appears likely that less than 10 pounds of VOCs were extracted from soil at the Site during this reporting period (see Table 4a).

#### 3.2.5. SCAOMD Compliance Monitoring

During this reporting period, the effluent of the treatment system was monitored with a PID on a weekly basis to demonstrate conformance with the limitations of the SCAQMD permit for the system. For treatment system monitoring, the PID was calibrated with 50 ppmv of hexane.

The vapor treatment components of the SVE system at the Site are owned by Drewelow, and the SCAQMD permit is held by Drewelow. Drewelow reports that effluent concentrations measured by the PID have been within the discharge limitations of the SCAQMD permit throughout the operation of the SVE system.

## 4. PLANNED ACTIVITIES FOR NEXT QUARTER

During the next quarter, the depth to groundwater in the monitoring wells at the Site will continue to be measured on a monthly basis. Samples of groundwater will be collected from each of the groundwater monitoring wells at the Site during June 2001. These samples will be analyzed for VOCs using EPA Method 8260B and for CCR Metals using EPA Methods 206.2, 200.7, 218.4, and 245.1.

Webb will continue to operate the SVE system at the Site during the next quarter. Flow rates, vacuum, and PID readings will be monitored at the extraction wells on a weekly basis during operation of the SVE system.

#### 5. SUMMARY

Gauging of the depth to the groundwater table was performed at the groundwater monitoring wells at the Site on 4 January, 22 February, and 8 March 2001. On the basis of these measurements, the predominant direction of groundwater flow appears to be toward the south-southeast under both the Webb and Reliable Steel properties. This estimated direction of groundwater flow is consistent with previous groundwater monitoring at the Site.

The only VOCs detected in the samples of groundwater collected at the Site on 8 March 2001 were TCE, c-1,2-DCE, 1,1-DCE, and toluene. Consistent with previous results, TCE was the chemical of concern detected with the greatest frequency (five of six samples) and at the highest concentration (23,000 ug/L in well MW-1). The concentrations of TCE, c-1,2-DCE, and 1,1-DCE detected in samples of the groundwater collected at the Site during March 2000 were within the ranges of concentrations detected during previous monitoring at the Site. The only detection of toluene (140 ug/L) was in the sample of groundwater collected from well MW-5. No VOCs were detected in the sample of groundwater collected from downgradient monitoring well MW-4.

As requested by the RWQCB in its meeting with Webb on 8 February 2001, the samples of groundwater collected at the Site during March 2001 were analyzed for CCR metals. Arsenic (5.6 to 320 ug/L), barium(19 to 150 ug/L), molybdenum (<50 to 1,100 ug/L), and zinc (12 to 25 ug/L) were the only metals detected in the samples of groundwater collected at the Site on 8 March 2001 (see Table 3). No other metals, including chromium, were detected in the samples of groundwater collected from the monitoring wells at the Site.

The SVE system at the Site has operated continuously since the restart of the system on 19 February 2001. PID readings from soil vapor samples collected at the extraction wells and vapor monitoring probes suggest that total VOC concentrations in the blower influent and each of the vapor wells decreased during this reporting period.

### 6. REFERENCES AND PREVIOUS REPORTS

Erler & Kalinowski, Inc., 5 February 2001. Quarterly Progress Report for October through December 2000 for the Jervis B. Webb Company of California Property, 5030 Firestone Boulevard, South Gate, California.

Erler & Kalinowski, Inc., 26 October 2000. Quarterly Progress Report for July through September 2000 for the Jervis B. Webb Company of California Property, 5030 Firestone Boulevard, South Gate, California.

Erler & Kalinowski, Inc., 30 November 2000. Report on Site Conditions, Local Hydrogeology, and Offsite Groundwater Production and Work Plan for Groundwater Remediation for the Jervis B. Webb Company Of California Property, 5030 Firestone Boulevard, South Gate, California.

Erler & Kalinowski, Inc., 26 October 2000. Quarterly Progress Report for July through September 2000 for the Jervis B. Webb Company of California Property, 5030 Firestone Boulevard, South Gate, California.

Erler & Kalinowski, Inc., 16 August 2000. Quarterly Progress Report for April through June 2000, Jervis B. Webb Company Property, 5030 Firestone Boulevard, South Gate, California.

Erler & Kalinowski, Inc., 27 April 2000. Quarterly Progress Report for January through March 2000, Jervis B. Webb Company Property, 5030 Firestone Boulevard, South Gate, California.

Erler & Kalinowski, Inc., 4 February 2000. Quarterly Progress Report for September to December 1999, Jervis B. Webb Company Property, 5030 Firestone Boulevard, South Gate, California.

Erler & Kalinowski, Inc., 13 October 1999. Quarterly Progress Report for July to August 1999, Jervis B. Webb Company Property, 5030 Firestone Boulevard, South Gate, California.

Erler & Kalinowski, Inc., 30 July 1999. Quarterly Progress Report for April to June 1999, Jervis B. Webb Company Property, 5030 Firestone Boulevard, South Gate, California.

Erler & Kalinowski, Inc., 4 June 1999. Quarterly Progress Report for January to March 1999, Jervis B. Webb Company Property, 5030 Firestone Boulevard, South Gate, California.

Erler & Kalinowski, Inc., 14 April 1999. Work Plan for Clarifier and Removal and Soil Remediation by Soil Vapor Extraction at the Jervis B. Webb Company Property Located at 5030 Firestone Boulevard, South Gate, California.

Erler & Kalinowski, Inc., 13 January 1999. Additional Groundwater Investigation and Quarterly Monitoring Report for October to December 1998, Jervis B. Webb Company Property, 5030 Firestone Boulevard, South Gate, California.

Erler & Kalinowski, Inc., 21 October 1998. Transmittal of Results for Additional Groundwater Investigation and Proposed Well Installation at 5030 Firestone Boulevard, South Gate, California.

Erler & Kalinowski, Inc., 29 September 1998. Project Tasks, Schedule, and Work Plan for Additional Groundwater Investigation and Quarterly Groundwater Monitoring at the Jervis B. Webb Company Property.

Erler & Kalinowski, Inc., 30 June 1998. Phase II Groundwater Investigation Report at 5030 Firestone Boulevard in South Gate, California.

Erler & Kalinowski, Inc., 18 February 1998. Phase II Soil Investigation Report for the Jervis B. Webb Company Property at 5030 Firestone Boulevard in South Gate, California.

Erler & Kalinowski, Inc., 20 June 1996. Phase I Environmental Site Assessment of the Jervis B. Webb Properties at 9301 Rayo Avenue and 5030 Firestone Boulevard in South Gate, California.

12

	45555	Elevation of	Depth to	Elevation of	
Well ID	Date	Top-of-Casing	Water	Water Surface	Comments
		(ft msi)	(ft bgs)	(ft msl)	
MW-1	2/27/98	106.09	44.79	61.30	
	3/2/98	106.09	44.82	61.27	
and the state of t	3/4/98	106.09	44.5B	61.51	
	4/8/98	106.09	44.57	61.52	
	5/20/98	106.09	43.99	62.10	
	10/8/98	106.09	43.38	62.71	
and the same of th	11/5/98	106.09	43.14	62.95	
	12/21/98	106.09	43.37	62.72	
	1/19/99	106.09	43.26	62.83	
	2/3/99	106.09	42.98	63.11	
	3/30/99	106.09	43.22	62.87	
	6/1/99	106.09	43.48	62.61	
	7/29/99	106.09	43.82	62.27	
	9/1/99	106.09	43.76	62.33	
	9/23/99	106.09	44,03	62.06	
	10/18/99	106.09	44.43	61.66	
	12/8/99	106.09	44.55	61.54	
	1/27/00	106.09	44,40	61.69	
	2/28/00	106.09	44.34	61.75	
	3/15/00	106.09	44.06	62.03	
	4/13/00	106.09	44.73	61.36	
	5/18/00	106.09	44.58	61.51	
	6/20/00	106.09	44.60	61.49	
	7/13/00	106.09	45.17	60.92	
	8/17/00	106,09	45.30	60.79	
	9/7/00	106.09	45.15	60.94	
	10/26/00	106.09	45.87	60.22	
	11/21/00	106.09	45.60	60.49	
	12/5/00	106.09	45.72	60.37	
The state of the s	1/4/01	106.09	45.67	60.42	
***************************************	2/22/01	106.09	45,43	60.66	
Openituring as a page	3/8/01	106.09	45.09	61.00	

		Elevation of	Depth to	Elevation of	
Well ID	Date	Top-of-Casing	Water	Water Surface	Comments
		(ft msl)	(ft bgs)	(ft msi)	
MW-2	2/27/98	106.65	44.02	62.63	
	3/2/98	106.65	44.06	62.59	
	3/4/98	106.65	44.13	62.52	
	4/8/98	106.65	NR		Truck parked on well.
	5/20/98	106.65	43.51	63.14	
	10/8/98	106.65	42.84	63.81	
	11/5/98	106.65	42.64	64.01	
	12/21/98	106,65	42.69	63.96	RANGE TO THE PARTY OF THE PARTY
	1/19/99	106.65	42.66	63.99	nare and a second a
	2/3/99	106.65	42.55	64,10	
	3/30/99	106.65	42.63	64.02	
İ	6/1/99	106.65	<b>42</b> .91	63.74	
	7/29/99	106.65	43,13	63.52	
	9/1/99	106.65	43.14	63.51	
	9/23/99	106.65	43,35	63.30	
:	10/18/99	106.65	43.60	63.05	
	12/8/99	106,65	43.62	63.03	distinctive and the second
	1/27/00	106.65	43.86	62.79	
	2/28/00	106.65	43.86	62.79	
	3/15/00	106.65	43.62	63.03	
	4/13/00	106.65	43.92	62.73	
	5/18/00	106,65	43.50	63.15	
	6/20/00	106,65	43.48	63,17	
	7/13/00	106.65	43.29	63.36	Avidant
	8/17/00	106.65	43.38	63.27	
	9/7/00	106.65	44.30	62,35	
	10/26/00	106.65	44.74	61.91	1
	11/21/00	106.65	44.52	62.13	
	12/5/00	106.65	44,51	62.14	
	1/4/01	106.65	44.55	62.10	### ### ### ### ### ### ### ### ### ##
	2/22/01	106.65	43.91	62.74	
	3/8/01	106.65	43.25	63,40	REPRESENTATION OF THE PROPERTY

		Elevation of	Depth to	Elevation of	***************************************
Well ID	Date	Top-of-Casing	Water	Water Surface	Comments
		(ft msl)	(ft bgs)	(ft msl)	
MW-3	2/27/98	105.87	44.55	61.32	
	3/2/98	105.87	44.56	61.31	
	3/4/9B	105.87	44.40	61.47	
	4/8/98	105.87	44.39	61.48	
	5/20/98	105.87	43.80	62.07	
	10/8/98	105.87	43.26	62.61	
	11/5/98	105.87	43.60	62.27	
	12/21/98	105.87	43.33	62.54	
	1/19/99	105.87	43.18	62.69	
	2/3/99	105.87	42.97	62.90	
	3/30/99	105.87	43.19	62.68	
	6/1/99	105.87	43.58	62.29	
	7/29/99	105.87	43.85	62.02	
	9/1/99	105.87	43.90	61.97	
	9/23/99	105.87	44.10	61.77	
	10/18/99	105.87	44.37	61.50	
	12/8/99	105.87	44.64	61.23	
	1/27/00	105.87	44.69	61.18	
	2/28/00	105.87	44.75	61.12	
	3/15/00	105,87	44,41	61.46	
	4/13/00	105.87	44.86	61.01	
	5/18/00	105.87	44.94	60,93	
1	6/20/00	105.87	44.88	60.99	
	7/13/00	105.87	45.25	60.62	
	8/17/00	105.87	45.06	60.81	
	9/7/00	105.87	44.83	61.04	
	10/26/00	105.87	45.94	59.93	
	11/21/00	105.87	46.00	59.87	
	12/5/00	105.87	45.77	60.10	
	1/4/01	105,87	45,89	59.98	
	2/22/01	105.87	45.53	60.34	
	3/8/01	105.87	45.21	60.66	

***************************************	111111111111111111111111111111111111111	Elevation of	Depth to	Elevation of	
Well ID	Date	Top-of-Casing	Water	Water Surface	Comments
		(ft msl)	(ft bgs)	(ft ms!)	
MW-4	11/3/98	104.72	42.77	61.95	Well Developed
	11/5/98	104.72	42.64	62,08	
	12/21/98	104.72	42.93	61.79	
	1/19/99	104.72	42.80	61.92	
	2/3/99	104.72	42.63	62.09	
	3/30/99	104.72	42.89	61.83	
	6/1/99	104.72	43.28	61.44	
	7/29/99	104.72	43.63	61.09	
	9/1/99	104.72	43.70	61.02	
	9/23/99	104.72	43.96	60.76	
	10/18/99	104.72	44.22	60.50	
	12/8/99	104.72	44.48	60.24	
	1/27/00	104.72	44.70	60.02	
	2/28/00	104.72	NR		Truck parked on well.
	3/15/00	104.72	44.37	60.35	·
	4/13/00	104.72	NR	shift tolar	Truck parked on well.
	5/18/00	104.72	44.81	59.91	
	6/20/00	104.72	44.94	59.78	
	7/13/00	104.72	45.10	59.62	
	8/17/00	104.72	45.36	59.36	
	9/7/00	104.72	45.31	59,41	
	10/26/00	104.72	45.89	58.83	
	11/21/00	104.72	45.86	58.86	
	12/5/01	104.72	45.71	59.01	
	1/4/01	104.72	45.79	58.93	
	2/22/01	104.72	45.49	59.23	
	3/8/01	104.72	45.62	59.10	

Quarterly Progress Report for January through March 2001

Jervis B. Webb Company of California, 5030 Firestone Boulevard, South Gate, California

		Elevation of	Depth to	Elevation of	***************************************
Well ID	Date	Top-of-Casing	Water	Water Surface	Comments
		(ft msl)	(ft bgs)	(ft msl)	- EXPERIENCE OF THE PROPERTY O
MW-5	11/3/98	106.13	43.32	62.81	Well Developed
	11/5/98	106,13	43.30	62.83	
	12/21/98	106.13	43.58	62.55	
	1/19/99	106.13	43.46	62.67	
	2/3/99	106.13	43.20	62.93	
	3/30/99	106.13	43.49	62.64	
	6/1/99	106.13	43.88	62.25	
	7/29/99	106.13	44.19	61.94	
	9/1/99	106,13	44.22	61.91	
	9/23/99	106.13	44.48	61.65	
	10/18/99	, 106.13	44.72	61.41	
	12/8/99	106.13	44.98	61.15	
	1/27/00	106,13	45.17	60.96	
	2/28/00	106.13	45.15	60.98	
	3/15/00	106.13	44.87	61.26	
	4/13/00	106.13	45.22	60.91	
	5/18/00	106.13	45.29	60.84	
	6/20/00	106.13	45.30	60.83	
	7/13/00	106.13	45.63	60,50	
	8/17/00	106.13	45,85	60,28	
	9/7/00	106.13	45.69	60.44	
	10/26/00	106.13	46.35	59.78	**************************************
	11/21/00	106.13	46.33	59.80	
	12/5/00	106.13	<b>46</b> .16	<b>5</b> 9.97	
	1/4/01	106.13	46.26	59.87	
	2/22/01	106.13	46.00	60.13	
	3/8/01	106.13	45.95	60.18	

NOTES:

ft msl = feet above mean sea level

ft bgs = feet beneath ground surface

NR = Not Recorded

-- Not Applicable

- 1. Monitoring well northing and easting coordinates and top-of-casing elevations for wells MW-1, MW-2, and MW-3 were surveyed on 6 March 1998 by Rattray & Associates, Inc.
- 2. Monitoring well northing and easting coordinates and top-of-casing elevations for wells MW-4 and MW-5 were surveyed on 21 December 1998 by Rattray & Associates, Inc.

# TABLE 2 Results of VOCs Detected in Groundwater Samples

Quarterly Progress Report for January through March 2001

Well ID	Sample Number	Sample									
AAGII ID	Sample Municiper	Date	Benzene	Toluene	1,1-DCA	1,1-DCE	1,2-DCA	c-1,2-DCE	t-1,2-DCE	PCE	TCE
MW-1	MW-1-0304	3/4/98	<100	<100	<100	220	<100	130	<100	140	24,000
	MW-1-0304DUP	3/4/98	<100	<100	<100	210	<100	150	<100	160	25,000
	MW-1-0520	5/20/98	<125	<125	<125	160	<125	130	<125	<125	24,000
	MW-1	11/5/98	<125	<125	<125	140	<125	160	<125	170	28,000
	MW-1	2/3/99	<125	<125	<125	130	<125	160	<125	160	27,000
	MW-1	6/1/99	<100	<100	<100	140	<100	190	<100	160	28,000
	MW-1	9/1/99	<100	<100	140	220	<100	200	<100	190	32,000
	MW-1	12/8/99	<250	<250	<250	<250	<250	<250	<250	<250	30,000
	MW-1-A <sup>(3)</sup>	12/8/99	<100	<100	110	150	<100	200	<100	160	33,000
	MW-1	3/15/00	<100	<100	<100	160	<100	230	<100	150	30,000
	MW-1	6/20/00	<100	<100	<100	<100	<100	<100	<100	<100	24,000
	MW-1	9/7/00	<100	<100	<100	<100	<100	<100	<100	<100	21,000
	MW-1	12/5/00	<100	<100	<100	<100	<100	<100	<100	<100	30,000
	MW-1	3/8/01	<100	<100	<100	<100	<100	<100	<100	<100	23,000
MW-2	MW-2-0304	3/4/98	<10	<10	13	34	<10	65	<10	<10	2,700
	MW-2-0520	5/20/98	<10	<10	14	38	<10	68	<10	<10	3,000
	MW-2	11/5/98	<10	<10	13	36	<10	68	<10	<10	3,200
	MW-2	2/3/99	<10	<10	13	36	<10	70	<10	<10	3,200
	MW-2	6/1/99	<10	<10	12	34	<10	68	<10	<10	2,800
	MW-2	9/1/99	<10	<10	16	49	<10	72	<10	<10	3,100
	MW-2	12/8/99	<13	<13	<13	<13	<13	57	<13	<13	2,400
	MW-2-A <sup>(3)</sup>	12/8/99	<10	<10	12	22	<10	63	<10	<10	2,600
	MW-2	3/15/00	<10	<10	<10	<10	<10	74	<10	<10	2,800
	MW-2	6/20/00	<10	<10	<10	<10	<10	46	<10	<10	2,000
	MW-2	9/7/00	<10	<10	<10	<10	<10	42	<10	<10	1,800
	MW-2	12/5/00	<10	<10	<10	<10	<10	50	<10	<10	2,300
	MW-2	3/8/01	<10	<10	<10	<10	<10	44	<10	<10	1,800
	MW-2-DUP	3/8/01	<10	<10	<10	<10	<10	42	<10	<10	1,600

# TABLE 2 Results of VOCs Detected in Groundwater Samples

Quarterly Progress Report for January through March 2001

Well ID	Sample Number	Sample				Analyte C	Concentrat	ion (ug/L)	WAR WAR A CONTROL OF THE STATE		Maninimann na ana ana ana ana ana ana ana ana
AAGII ID	gampia Mumber	Date	Benzene	Toluene	1,1-DCA	1,1-DCE	1,2-DCA	c-1,2-DCE	t-1,2-DCE	PCE	TCE
E-WM	MW-3-0304	3/4/98	<10	13	14	82	<10	200	<10	<10	2,800
	MW-3-0520	6/20/98	<10	<10	13	58	<10	230	15	<10	2,800
	MW-3	11/5/98	<10	<10	11	66	<10	240	18	<10	2,300
	MW-3	2/3/99	<10	<10	11	64	<10	220	18	<10	2,000
	MW-3	6/1/99	<10	<10	11	66	53	240	18	<10	1,900
	MW-3	9/1/99	<10	<10	13	80	<10	<b>27</b> 0	20	<t0< td=""><td>2,600</td></t0<>	2,600
	MW-3	12/8/99	<13	<13	<13	<13	<13	220	<13	<13	2,500
	MW-3-A <sup>(3)</sup>	12/8/99	<10	<10	13	55	<10	240	19	<10	2,900
	MW-3	3/15/00	<10	<10	11	61	<10	300	20	<10	3,100
	MW-3	6/20/00	<10	<10	10	<10	<10	170	14	<10	1,900
	MW-3-DUP	6/20/00	<10	<10	11	<10	<10	200	16	<10	2,100
	MW-3	9/7/00	<10	<10	<10	<10	<10	160	<10	<10	1,700
	MW-3-DUP	9/7/00	<10	<10	<10	<10	<10	160	<10	<10	1,700
	MW-3	12/5/00	<10	<10	<10	<10	<10	200	<10	<10	2,400
	MW-3-DUP	12/5/00	<10	<10	20	<10	<10	210	<10	<10	2,500
	MW-3	3/8/01	<10	<10	<10	55	<10	200	<10	<10	1,700
MW-4	MW-4	11/5/98	<0,5	<0.5	<0.5	<0.5	<0.5	0. <b>67</b>	<0,5	<0.5	6.7
	MW-4	2/3/99	<0.5	<0.5	<0.5	<0.5	2.1	<0,5	<0.5	<0,5	<0. <del>5</del>
	MW-4	6/1/99	<0.5	<0.5	<0.5	<0.5	65	1.1	<0.5	<0.5	0.90
	MW-4	9/1/99	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5
	MW-4	12/8/99	1.2	<0.5	<0,5	<0.5	<0.5	4.1	1.0	<0.5	17
	MW-4-A <sup>(3)</sup>	12/8/99	1.2	<0.5	<0.5	<0.5	<0.5	4.6	1,1	<0.5	18
	MW-4	3/15/00	77	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	0.68
	MW-4	6/20/00	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5
	MW-4	9/7/00	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5
	MW-4	12/5/00	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5
	MW-4	3/8/01	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5

# TABLE 2 Results of VOCs Detected in Groundwater Samples

Quarterly Progress Report for January through March 2001

Jervis B. Webb Company of California, 5030 Firestone Boulevard, South Gate, California

Well ID	Sample Number	Sample				Analyte C	Concentrat	ion (ug/L)	MANAGEMENT OF THE PROPERTY OF	,	
Menin	Dambie Mannoal	Date	Benzene	Toluene	1,1-DCA	1,1-DCE	1,2-DCA	c-1,2-DCE	t-1,2-DCE	PCE	TCE
MW-5	MW-5	11/5/98	<25	<25	<25	42	<25	380	30	<25	5,000
	MW-5-DUP	11/5/98	<25	<25	<25	40	<25	360	29	<25	4,800
	MW-5	2/3/99	<25	<25	<25	49	<25	420	35	<25	5,100
	MW-5-DUP	2/3/99	<25	<25	<25	45	<25	370	31	<25	4,500
	MW-5	6/1/99	<25	<25	<25	52	35	420	36	<25	5,500
	MW-5-DUP	6/1/99	<25	<25	<25	56	39	430	35	<25	5,300
	MW-5	9/1/99	<25	<25	<25	40	<25	420	45	<25	5,500
	MW-5-DUP	9/1/99	<25	<25	<25	69	<25	440	45	<25	6,000
	MW-5	12/8/99	<50	<50	<50	<50	<50	390	<50	<50	5,100
	MW-5-A <sup>(3)</sup>	12/8/99	<25	<25	<25	<25	<25	410	25	<25	5,300
	MW-5-DUP	12/8/99	<50	<50	<50	<50	<50	360	<50	<50	5,000
	MW-5-DUP-A <sup>(3)</sup>	12/8/99	<25	<25	<25	<25	<25	410	26	<25	5,300
	MW-5	3/15/00	<b>&lt;5</b> 0	<50	<50	<50	<50	440	<50	<50	5,500
	MW-5-DUP	3/15/00	<50	<50	<50	<50	<50	450	<50	<50	5,800
	MW-5	6/20/00	<25	<25	<25	<25	<25	350	<25	<25	4,400
	MW-5	9/7/00	<10	<10	<10	<10	<10	280	<10	<10	3,700
	MW-5	12/5/00	<10	<10	<10	<10	<10	190	<10	<10	4,700
	MW-5	3/8/01	<25	140	<25	<25	<25	260	<25	<25	3,600

NOTES:

1,1-DCA = 1,1-dichloroethane

1,1-DCE = 1,1-dichloroethene

1,2-DCA = 1,2-dichloroothane

c-1,2-DCE = cis-1,2-dichloroethene

t-1,2-DCE = trans-1,2-dichloroethene

PCE = tetrachloroethene

TCE = trichloroethene

VOCs = volatile organic compounds

ug/L = micrograms per liter

- 1. Analyses performed by Orange Coast Analytical, Inc., in Tustin, California, using EPA Method 8260 for VOCs.
- < indicates that the analyte was not detected at a concentration above the indicated method detection limit.</li>
- Samples collected on 8 December 1999 were initially analyzed on 9 December 1999 and were re-analyzed on 17 December 1999 in an attempt to achieve lower method detection limits.

## TABLE 3

# Additional Analytical Results for Groundwater Samples

Quarterly Progress Report for January through March 2001

Jervis B. Webb Company of California, 5030 Firestone Boulevard, South Gate, California

Well ID	Sample Number	Sample	mple Analyte Concentration (mg/L)									
44611 1T)	29unhia lamina	Date	Arsenic	Barium	Chromium	Chromium VI	Molybdenum	Zinc	TDS			
MW-1	MW-1-0520	5/20/98	ė n	4-	ние	e- e-	The second secon	-	1,500			
	MW-1	3/8/01	0,32	0.13	<0.01	<0.01	0.47	0.016	With-			
MW-2	MW-2-0520	5/20/98		alia hij	. ·				2,500			
	MW-2	3/8/01	0.0066	0.019	<0.01	<0.01	1.1	0.015				
	MW-2-DUP	3/8/01	0.0056	0.019	<0.01	<0.01	1.1	0.014				
MW-3	MW-3-0520	5/20/98		- MOVE	MARK	who	WW.	**	1,100			
	MW-3	3/8/01	0.080	0.15	<0.01	<0.01	0.71	0.012	ma.			
MW-4	MW-4	3/8/01	0.0079	0.027	<0.01	<0.01	<0.05	0.025	-4			
MW-5	MW-5	3/8/01	0.19	0.15	< 0.01	<0.01	0,84	0.014	42.44			

NOTES:

TDS = total dissolved solids

- indicates not analyzed

mg/L = milligrams per liter

Total Arsenic by EPA Method 206,2, CCR Metals by EPA Methods 200.7, 218,4, and 245,1, and TDS by EPA Method 160.1.

2. < indicates that the analyte was not detected at a concentration above the indicated method detection limit.

<sup>1.</sup> The following analyses were performed by Orange Coast Analytical, Inc., in Tustin, California:

# TABLE 4a Soil Vapor Extraction Data: Blower Influent

Quarterly Progress Report for January through March 2001

-		Elapsed		Fic	ow.		Total	TCE		nated	Cumulative Mass		
		Time on	Operation			Vacuum	;	Conc.	VOC R	emoval	F	<del>Remova</del>	I T
Date	Time	Hour Meter (hrs)	Time	(acfm)	(scfm)	(in-wc)	by PID (ppmv)	by Lab	TCE (lb/day)	Total VOCs (lb/day)	TCE (lbs)	Total VOCs (lbs)	Notes
All the state of t	System	startup o	n 3/16/00 at	t 16:00.									
3/16/00	16:45	5.6	0%	4.5	4.1	35	2,000+	860	1.8	1.9	0	0	
3/17/00	7:00	20	100%	5.2	4.7	37	94	-					
3/18/00	6:30	45	100%	5.4	4.9	38	128	-					
	System shut down on 3/18/00 at 9:40. System restarted on 3/19/00 at 6:30.												
3/19/00	6:30	48	13%	6.1	5.53	38	103	_					
3/20/00	6:30	72	100%	8.6	7.7	43	145						
3/21/00	7:00	96	100%	4.8	4.1	60	745	-					
3/22/00	7:30	121	100%	11	10	15	173	490	2.5	2.6	<b>1</b> 0	11	4A
3/30/00	11:00	316	100%	20	18	45	39	-					
4/6/00	11:00	483	100%	25	17	125	42	-					
4/13/00	8:00	648	100%	21	13	150	42	70	0.45	0.51	43	45	4A
4/20/00	7:30	815	100%	21	13	145	43	-					
4/27/00	7:00	983	100%	16	10	150	30	-					
5/4/00	8:30	1,152	100%	16	10	150	20	-					
5/11/00	6:30	1,318	100%	14	9.0	150	20	-					
5/18/00	7:00	1,486	100%	19	12	150	38	53	0.32	0.34	56	60	4A
				28	16	150	38	-	0.47	0.50		-	
5/25/00	6;30	1,654	100%	18	12	150	19						
6/1/00	6:30	1,822	100%	18	11	150	34	-					
6/8/00	7:00	1,990	100%	26	16	155	27	-					
6/15/00	7:30	2,158	100%	26	16	150	28	164					
	System	shut dow	n on 6/21/0	0 at 17:	30. Sy:	stem resta	arted on	7/6/00 at	10:00.				
7/6/00	10:23	2,312	30%	142	97	130	20	37	1.8	2,1	72	77	48
7/13/00	12:00	2,485	102%	122	79	145	23	18	0.70	1.0	81	88	4A
7/20/00	7:30	2,648	100%	<b>1</b> 15	73	150	15	-					
	System	shut dow	n on 7/26/0	0 at 6:3	0. Syst	tem restar	ted on 7	7/27/00 at	6:00.				
7/27/00	6:00	2,791	<b>8</b> 6%	75	49	140	14	-					
8/3/00	8:00	2,961	100%	75	49	140	15	-		-ty-ty-mornana			
8/8/00	14:30	3,086	100%	77	50	140	15	-					
	System	shut dov	n on 8/15/0	0 at 11:	30. Sy:	stem resta	arted on	8/21/00 :	at 10:30.	,			
8/24/00	12:30	3,326	63%	76	50	140	27	-					
	System		n on 8/30/0		30. Sys	stem resta	rted on	8/31/00 :	at 9:00.				
8/31/00	9:00	3,471	88%	64	45	120	36	_		Maria Maria			

# **TABLE 4a**

# Soil Vapor Extraction Data: Blower Influent

Quarterly Progress Report for January through March 2001

		Elapsed Time on		Flo	ρW	Vacuum	Total	TCE	Estin VOC R	nated emoval	Cumulative Mass Removal		Į
Date	Time	Hour Meter (hrs)	Operation Time	(acfm)	(scfm)	Vacuum (in-wc)	by PID (ppmv)	_	TCE (lb/day)	Total VOCs (lb/day)	TCE (lbs)	Total VOCs (ibs)	Notes
	System	shut dow	/n on 9/6/00	at 15;0	0. Syst	tem restar	ted on 9	9/7/00.			***************************************		
9/7/00	10:30	3,621	88%	66	46	125	9.7	•					
9/14/00	9:00	3,788	100%	66	43	140	13	5.6	0.12	0.29	104	124	4A
	System	shut dow	/n on 9/14/0	0 for re	bound	test.							
9/28/00	11:24	3,788	0%	-		120	42	54	<b></b>	-	**	-	l
System shut down on 9/28/00 at 12:00. System restarted on 10/1/00 at 6:30.													
10/1/00	6:30	3,791	4%	*	**	_	-	-					
,	System	shut dow	n on 10/1/0	0 at 10:	30. Sy	stem resta	arted on	10/5/00 a	at 7:30.				
10/5/00	7:30	3,795	4%	73	52	120	296	-					
10/12/00	8:00	3,964	100%	74	52	120	39	-					
10/19/00	8:00	4,132	100%	72	51	120	39	~					
10/26/00	8:00	4,301	100%	75	54	115	18	2.3	0.061	0.15	106	128	4A
}	System	shut dow	/n on 10/31.	00 at 9:	20. Sy:	stem resta	arted on	11/2/00	at 8:00.				MARAMINI
11/2/00	8:00	4,422	72%	***	**	140	17	-					ewoninates
	System	shut dov	/n on 11/2/0	0 at 19:	:00. Sy:	stem resta	arted on	11/9/00	at 7:30.				1
11/9/00	7: <b>3</b> 0	4,433	7%	*		140	397	-					Militheanne
	System	shut dow	/n on 11/9/0	0 at 15:	30. Sy	stem resta	arted on	11/16/00	at 10:00	).			1
11/16/00	10:00	4,441	5%	•	:==c	140	144	-					
-	System	shut dow	n on 11/17	00 at 1	2:00. S	ystem res	tarted o	n 11/23/0	0 at 7:30	).			Ì
11/23/00	7:30	4,443	1%		••	140	152	_					
11/30/00	7:30	4,611	100%	-	****	140	121	•					
	System	shut dow	/n on 12/6/0	0 at 21:	:00. <b>S</b> ys	stem resta	arted on	12/7/00	at 8:00.				
12/7/00	8:00	4,768	93%	-	**	140	107	_		MANAGEMENT AND A STATE OF THE S			
12/14/00	10:30	4,940	100%	57	38	140	6.2	6.7	0.13	0.23	108	133	4A
	System shut down on 12/14/00 for rebound test.												
1/4/01	11:37	<b>4,94</b> 0	0%	170	111	140	44	30	-	uu .	.es	·	

## **TABLE 4a**

# Soil Vapor Extraction Data: Blower Influent

Quarterly Progress Report for January through March 2001

Jervis B. Webb Company of California, 5030 Firestone Boulevard, South Gate, California

		Elapsed Time on	1	Flo	DW	1 ' ' 1	Total	TCE	Estimated VOC Removal	l	ulative N Removal	
Date	Time	Hour Meter (hrs)	Operation Time	(acfm)	(scfm)		VOCs by PID (ppmv)	-	TCE Total (lb/day) (lb/day)	TCE (lbs)	Total VOCs (ibs)	Notes
	System	shut dow	/n on 1/4/01	. Syste	em resta	arted on 2	/19/01 at	15:45.		#14141	H990LH444	***************************************
2/19/01	15:45	4,940	0%	-	-	140	42	-				
2/22/01	17:00	5,016	100%	-	-	140	37	-				
3/1/01	12:45	5,180	100%	-	ini	140	29	-				
3/8/01	7:30	5,343	100%	-	=	145	48	-				
3/15/01	13:00	5,516	100%		-	145	8.5	-				
3/22/01	13:00	5,682	100%			145	7.8	•				
3/29/01	14:30	5,854	100%	**	-	140	8.5	-				-

#### NOTES:

TCE = trichloroethene

acfm = actual cubic feet per minute

°F = degrees Fahrenheit

hrs = hours

in-wc = inches of water column

lb/day = pounds per day

ibs = pounds

PID = photoionization detector

ppmv = parts per million by volume

scfm = standard cubic feet per minute

tr = trace (concentration detected at less than reporting limit)

VOCs = volatile organic compounds

- = no measurement

< = not detected at indicated method detection limit

- 1. PID calibrated with 100 ppmv of isobutylene.
- Laboratory analyses were performed by Performance Analytical, Inc. in Simi Valley, California using EPA Method TO-14A.
- 3. Removal rates are calculated using analyte concentrations from laboratory analyses and the measured flow rate (converted from acfm to sofm using the measured vacuum).
- 4. Cumulative mass removal amounts are calculated as follows (see Notes column in table):
  - A: Mass removal calculated using an average of the previous and current mass removal rates.
  - B: Mass removal calculated using the previous mass removal rate.
- 5. On days for which two flow and vacuum readings are provided, the values indicate initial and final readings during the site visit.
- 6. Although not shown on this table, mass removal rates were calculated for each VOC detected in the samples of undiluted blower influent. The total VOC mass removal rate presented in this table is the sum of the undiluted mass removal rates calculated for each VOC that was detected.

# TABLE 4b

# Soil Vapor Extraction Data: Extraction Well SVE-1

Quarterly Progress Report for January through March 2001

			FI	ow.				1	ted VOC	ì	ulative l	
		Elapsed				Total	TCE	Remov	al Rates		Remova	<u> </u>
Date	Time	Time on Hour Meter (hrs)	(acfm)	(scfm)	(in-wc) by	VOCs by PID (ppmv)	Conc. by Lab (ppmv)	TCE (lb/day)	Total VOCs (lb/day)	TCE (lbs)	Total VOCs (lbs)	Notes
	Static va	por samp	le colle	cted on	3/16/00.							
3/16/00	9:25	5.6	0.04	0.04	35	865	10,000	0.18	0.19	0	0	
	System :	startup or	3/16/00	at 16:0	0.							
3/17/00	7:00	20	0.04	0.04	37	191	-					
3/18/00	6:30	45	0.06	0.05	38	195	-					
	System :	shut dow	n on 3/18	B/00 at 9	:40. Syst	em resta	rted on 3/	19/00 at 6	:30.			
3/19/00	6:30	48	0.70	0.63	38	2,000+	-					
3/20/00	6:30	72	0.63	0.56	43	2,000+	-					
3/21/00	7:00	96	0.61	0.52	60	2,000+	~					
3/22/00	7:30	121	0.58	0.56	15	2,000+	10,000	2.8	2.9	7.1	7.3	4A
3/30/00	11:00	316	0.87	0.79	38	1,799	-					
4/6/00	11:00	483	0.45	0.31	125	719	-					
4/13/00	8:00	648	0.85	0.54	150	716	6,500	1.7	1.8	57	58	4A
4/20/00	7:30	815	0.70	0.45	145	868	-					
4/27/00	7:00	983	0.87	0.55	150	915	-					
5/4/00	8:30	1,152	0.89	0.56	150	1,427	-					
5/11/00	6:30	1,318	0.92	0.58	150	2,000+	0.700	4.0	d M	400	440	4.0
5/18/00	7:00	1,486	1.1	0.68 0.69	150 150	276 276	3,700	1.2	1.3	109	112	4A
5/25/00	6:30	1,654	1.1 1.3	0.84	150	146	~	1.3	1,3	-	-	
6/1/00	6:30	1,822	0.65	0.41	150	128						
6/8/00	7:00	1,990	0.67	0.41	155	112	_					
6/15/00	7:30	2,158	0.65	0.41	150	105	-					
							sample c	; collected o	in 7/6/00.			
7/6/00	9:49	2,312	1.3	0.89	130	1,582	3,300		-	-	~	
	System	restarted	•		1							
7/13/00	12:00	2,485	1.3	0.84	145	2,000+	2,200	0.92	0.95	154	159	4A
7/20/00	7:30	2,648	1.3	0.83	150	154	-					
System shut down on 7/26/00 at 6:30. System restarted on 7/27/00 at 6:00.												
7/27/00	6:00	2,791	2.0	1.3	140	77				ne n		
8/3/00	00:8	2,961	2.1	1.4	140	89	~					
8/8/00	14:30	3,086	2.1	1.4	140	92	-					
	System:	shut dowi	n on 8/1	5/00 at 1	1:30. Sys	stem rest	arted on	8/21/00 at	10:30.			

## **TABLE 4b**

# Soil Vapor Extraction Data: Extraction Well SVE-1

Quarterly Progress Report for January through March 2001

Jervis B. Webb Company of California, 5030 Firestone Boulevard, South Gate, California

	***************************************	Elapsed	Fi				1	ted VOC		ulative l		
		Time on		r		Total	TÇE	Remov	al Rates		Remova	l
Date	Time	Hour Meter (hrs)	(acfm)	(scfm)	(in-wc)	VOCs by PID (ppmv)	Conc. by Lab (ppmv)	TCE (lb/day)	Total VOCs (lb/day)	TCE (lbs)	Total VOCs (lbs)	Notes
8/24/00	12:30	3,326	2.3	1.5	140	622	_		***************************************			PROFESSION 1
	System	shut dowr	1 on 8/30	0/00 at 1	3:30. Sy:	stem rest	arted on	, 8/31/00 at :	9:00.			
8/31/00	9:00	3,471			120							
	System :	shut dow	1 on 9/6/	00 at 15	: :00. Syst	tem resta	rted on 9	/7/00.				
9/7/00	10:30	3,621	1.1	0.78	125	62						
9/14/00	9:00	3,788	1.6	1.0	140	76	300	0.15	0.16	183	189	4A
	System:	shut dow	on 9/1	4/00 for	rebound	test. Stat	ic vapor	sample co	llected on	9/28/00.		,
9/28/00	11:07	3,788	1.6	1.1	120	2,000+	230	-	•	-	•••	
	System	shut dow	n on 9/2	8/00 at 1	2:00. Sy	stem rest	arted on	10/1/00 at	6: <b>30</b> .			
10/1/00	6:30	3,791	_	-	-		-					
	System	shut dowr	on 10/	1/00 at 1	0:30. Sy	stem rest	arted on	10/5/00 at	7:30.			
10/5/00	7:30	3,795	2.3	1.6	120	2,000+	-					
10/12/00	8:00	3,964	2.4	1,7	120	1,687	***					
10/19/00	8:00	4,132	2.4	1.7	120	651	-					
10/26/00	8:00	4,301	2.4	1.7	115	385	140	0.12	0.12	186	192	4A
	_						arted on	11/2/00 at i	B: <b>00</b> .			
11/2/00	8:00	4,422	3.6	2.4	140	289	-					
	System	shut dowr	on 11/2					11/9/00 at	7:30.			
11/9/00	7:30	4,433	2.5	1.6	140	2,000+						
AAATATA AAAAAAAAAAAAAAAAAAAAAAAAAAAAAA	System	shut dow	on 11/	9/00 at 1	5;30. Sys	stem rest	arted on	11/16/00 at	10:00.			
11/16/00	10:00	4,441	2.7	1.7	140	2,000+	-					
	System:	shut dow	on 11/	17/00 at	12:00. St	ystem res	tarted on	11/23/00 a	at 7:30.			
11/23/00	7:30	4,443	2.5	1.7	140	2,000+	to:					
11/30/00	7:30		•		140	,	-					
1	-						arted on	12/7/00 at 1	8:00.	- no very proposition		
12/7/00	8:00	4,768	8.3	5.4	140	111	-					
12/14/00	10:30	4,940	2.4	1.6	140	43	260	0.21	0.22	191	197	4A
	-	shut dow										
1/4/01	11:02	4,940	2.3	1.6	120	515	350	-	FF.		-	

30 April 2001

## TABLE 4b

# Soil Vapor Extraction Data: Extraction Well SVE-1

Quarterly Progress Report for January through March 2001

Jervis B. Webb Company of California, 5030 Firestone Boulevard, South Gate, California

		Elapsed	Flow			Total	TCE		ed VOC al Rates		ulative l Remova	
Date	Time	Time on Hour Meter (hrs)	(acfm)	(scfm)	Vacuum (in-wc)	VOCs by PID (ppmv)	Conc. by Lab (ppmv)	TCE (lb/day)	Total VOCs (lb/day)	TCE (lbs)	Total VOCs (ibs)	Notes
	System shut down on 1/4/01. System restarted on 2/19/01 at 15:45.											
2/19/01	15:45	4,940	2.5	1.6	140	875	-					
2/22/01	17:00	5,016	2.6	1.7	140	801						
3/1/01	12:45	5,180	2.5	1.7	140	1,505	-					
3/8/01	7:30	5,343	2.5	1.6	145	79	**					
3/15/01	13:00	5,516	2.5	1.6	145	37	-					
3/22/01	13:00	5,682	2.6	1.6	145	53	*					
3/29/01	14:30	5,854	2.3	1.6	130	38	~	-	edo e	_	_	

#### NOTES:

TCE = trichloroethene

acfm = actual cubic feet per minute

°F = degrees Fahrenheit

hrs = hours

in-wc = inches of water column

lb/day = pounds per day

lbs = pounds

PID = photoionization detector

ppmv = parts per million by volume

scfm = standard cubic feet per minute

tr = trace (concentration detected at less than reporting limit)

VOCs = volatile organic compounds

- = no measurement

< = not detected at indicated method detection limit

- 1. PID calibrated with 100 ppmv of isobutylene.
- 2. Laboratory analyses were performed by Performance Analytical, Inc. in Simi Valley, California using EPA Method TO-14A.
- 3. Removal rates are calculated using analyte concentrations from laboratory analyses and the measured flow rate (converted from acfm to scfm using the measured vacuum).
- 4. Cumulative mass removal amounts are calculated as follows:
  - A: Mass removal calculated using an average of the previous and current mass removal rates.
- 5. On days for which two flow and vacuum readings are provided, the values indicate initial and final readings during the site visit.
- 6. Although not shown on this table, mass removal rates were calculated for each VOC detected in the samples collected from well SVE-1. The total VOC mass removal rate presented in this table is the sum of the mass removal rates calculated for each VOC that was detected.
- 7. Extraction well SVE-1 is screened in the shallow vadose zone from 19 to 25 feet below ground surface.

# **TABLE 4c**

# Soil Vapor Extraction Data: Extraction Well SVE-2

Quarterly Progress Report for January through March 2001

-	**************************************	Elapsed		)W	M	Total	TCE		ed VOC al Rates	1	ulative Remova	
Date	Time	Time on Hour Meter (hrs)	(acfm)	(scfm)	(in-wc) by PID (ppmv)	Gonc. by Lab (ppmv)	TCE (lb/day)	Total VOCs (lb/day)	TCE (lbs)	Total VOCs (lbs)	Notes	
	Static va	ipor samp	le collec	ted on	3/16/00.							
3/16/00	10:10	5.6	0.61	0,56	35	227	75	0.021	0.021	0	0	
	System	Startup or	3/16/00	at 16:0	0.							
3/17/00	7:00	20.3	0.61	0.55	37	191	-					
3/18/00	6:30	44.7	0.61	0.55	38	33	-					
	System	shut dow	on 3/18	3/00 at 9	:40. Syst	em resta	rted on 3	/19/00 at 6:	30.			
3/19/00	6:30	47.9	0.65	0.59	38	298						
3/20/00	6:30	72.2	0.94	0.84	43	235	~					
3/21/00	7:00	96.3	0.89	0.76	60	227	-					
3/22/00	7:30	120.5	0.57	0.55	15	93	-					
3/30/00	11:00	316	0.59	0.53	38	78	-					
4/6/00	11:00	483	0.74	0.51	125	38	-					
4/13/00	8:00	648	2.5	1.6	<b>1</b> 50	26	+46.					
4/20/00	7:30	815	1.1	0.71	145	5.4	-					
4/27/00	7:00	983	2.4	1.5	150	2.7						
5/4/00	8:30	1,152	2.3	1.5	150	5.8	-					
5/11/00	6:30	1,318	2.2	1.4	150	5.2	-					
5/18/00	7:00	1,486	2.2	1.4	150	13	.,					
			2.0	1.3	150	13	.444					
5/25/00	6:30	1,654	2.1	1.3	150	<b>6</b> .8						
6/1/00	6:30	1,822	2.1	1.3	150	28	-					
6/8/00	7:00	1,990	2.1	1.3	155	42	-					
6/15/00	7:30	2,158	2.1	1.3	150	38	-					
	System	shut dowi	on 6/2	1/00 at 1	7:30. Sta	tic vapor	sample (	collected o	n 7/6/00.			
7/6/00	9:25	2,312	1.2	0.83	130	37	120	0.050	0.054	3.4	3.6	4A
- Contraction of the Contraction	System	restarted	on 7/6/0	0 at 10:0	0.							
7/13/00	12:00	2,485	1.3	0.80	145	6.8	<u></u>					
7/20/00	7:30	2,648	1.3	0.80	150	27	•					
1					,		rted on 7.	' /27/00 at 6:	00.			
7/27/00	6:00	2,791	1.6	1.1	140	18						
8/3/00	7:30	2,961	1.6	1.0	140	17	_					
8/8/00	14:30	3,086	1,6	1,0	140	14	_					
					! !		i arted on i	। 8/21/00 at <sup>-</sup>	f∩∙ <b>ว</b> ก			
1	12:30						wited VII	ببد ۱:۷ <b>۷ وا</b>	1 W. UU.			
8/24/00	12:3U	3,326	1.9	1.2	140	1.7		т т т т т т т т т т т т т т т т т т т			mananiii Military ee	

# **TABLE 4c**

# Soil Vapor Extraction Data: Extraction Well SVE-2

Quarterly Progress Report for January through March 2001

Historia han managaran and a papagaran and a p	**************************************	Elapsed	Flo	DW	Vacuum '	T 4 1	TCE	1	ted VOC al Rates	ł	ulative Remova	
Date	Time	Time on Hour Meter (hrs)	(acfm)	(scfm)		Total VOCs by PID (ppmv)	Conc. by Lab (ppmv)	TCE (lb/day)	Total VOCs (lb/day)	TCE (lbs)	Total VOCs (lbs)	Notes
	System	shut dowr	on 8/3	0/00 at 1	3:30. Sy:	stem rest	arted on	8/31/00 at :	9:00.		***************************************	
8/31/00	9:00	3,471	1.5	1.1	120	22	-					
MMMMM Annual Ann	System	shut dowr	on 9/6/	00 at 15	: i:00. Syst	em resta	rted on 9	/7/00.				
9/7/00	10:30	3,621	1.6	1,1	125	16	***			MARIE DE LA CONTRACTOR DE		
9/14/00	9:00	3,788	1.6	1.1	140	20	77	0.041	0.042	6.2	6.5	4A
	System	shut dowr	on 9/1	4/00 for	rebound	test. Stat	tic vapor	sample co	llected on	9/28/00.		
9/28/00.	10:50	3,788	1.4	1.0	120	61	110.	_	-	_	Your	
	System	shut dowr	on 9/2	B/00 at 1	2:00. Sys	stem rest	arted on	10/1/00 at (	<b>6</b> :30.			
10/1/00	6:30	3,791	_	-	-	-	-					
	System	shut dowr	1 on 10/	1/00 at 1	0:30. Sys	stem rest	arted on	10/5/00 at '	7:30.			
10/5/00	7:30	3,795	1.9	1.4	120	9.7	-					ļ
10/12/00	8:00	3,964	1.9	1.4	120	97	-					
10/19/00	8:00	4,132	1.9	1.3	120	33	-					
10/26/00	8:00	4,301	2.1	1.5	115	28	hds.					
	System	shut dowr	on 10/3	31/00 at	9:20. Sys	stem rest	arted on	11/2/00 at	B:00 <i>.</i>			
11/2/00	8:00	4,422	-	ter	140	6.0						i
	System	shut dowr	on 11/2	2/00 at 1	9:00. Sy:	stem rest	arted on	11/9/00 at	7:30.			
11/9/00	7:30	4,433	-	**	140	8.2	-					
	System	shut dowr	on 11/9	9/00 at 1	5:30. Sys	stem rest	arted on	11/16/00 at	L 10:00.			
11/16/00	10:00	4,441	_	-	140	810						
	System	shut dowr	on 11/	17/00 at	12:00. S	ystem res	started on	11/23/00 :	at 7:30.			
11/23/00	7:30	4,443	_	**	140	7,5	-					
11/30/00	7:30	4,611		**	140	5.3	-					
	System	shut dowr	on 12/	6/00 at 2	1:00. Sy:	stem rest	arted on	12/7/00 at	B:00.			
12/7/00	8:00	4,768	-	-	140	40	-					
12/14/00	10:30	4,940	2.9	1.9	140	9.7	29	0.027	0.029	7.8	8.2	4A
	System	shut dowr	on 12/	14/00 fo	r rebound	l test.						
1/4/01	10:20	4,940	1.9	1.3	120	25	34	Here	79%	_	_	

### TABLE 4c

# Soil Vapor Extraction Data: Extraction Well SVE-2

Quarterly Progress Report for January through March 2001

Jervis B. Webb Company of California, 5030 Firestone Boulevard, South Gate, California

		Elapsed Flow Total	TCE	Estimated VOC Removal Rates		Cumulative Mass Removal						
Date	Time	Time on Hour Meter (hrs)	(acfm)	(scfm)	Vacuum (in-wc)	VOCs by PID (ppmv)	Conc. by Lab (ppmv)	TCE (lb/day)	Total VOCs (lb/day)	TCE (lbs)	Total VOCs (lbs)	Notes
***************************************	System	shut dowr	on 1/4	/01. Sys	tem resta	rted on 2	2/19/01 at	15:45.			igo	
2/19/01	15:45	4,940	-	*	140	38	-					
2/22/01	17:00	5,016	-	-	140	46	-					
3/1/01	12:45	5,180	-	where	140	61						
3/8/01	7:30	5,343		**	145	33	-					
3/15/01	13:00	5,516	sa-	-	145	5.8	~					
3/22/01	13:00	5,682	-	••	145	3.7	-					
3/29/01	14:30	5,854	~	-	140	7.5	-	ì <u>-</u>	*	=		

#### NOTES:

TCE = trichloroethene

acfm = actual cubic feet per minute

°F = degrees Fahrenheit

hrs = hours

in-wc = inches of water column

ib/day = pounds per day

ibs = pounds

PID = photoionization detector

ppmv = parts per million by volume

scfm = standard cubic feet per minute

tr = trace (concentration detected at less than reporting limit)

VOCs = volatile organic compounds

= no measurement

< = not detected at indicated method detection limit

- 1. PID calibrated with 100 ppmv of isobutylene.
- 2. Laboratory analyses were performed by Performance Analytical, Inc. in Simi Valley, California using EPA Method TO-14A.
- 3. Removal rates are calculated using analyte concentrations from laboratory analyses and the measured flow rate (converted from acfm to scfm using the measured vacuum).
- 4. Cumulative mass removal amounts are calculated as follows:
  - A: Mass removal calculated using an average of the previous and current mass removal rates.
- 5. On days for which two flow and vacuum readings are provided, the values indicate initial and final readings during the site visit.
- 6. Although not shown on this table, mass removal rates were calculated for each VOC detected in the samples collected from well SVE-2. The total VOC mass removal rate presented in this table is the sum of the mass removal rates calculated for each VOC that was detected.
- 7. Extraction well SVE-2 is screened in the shallow vadose zone from 18 to 24 feet below ground surface.

# TABLE 4d

# Soil Vapor Extraction Data: Extraction Well SVE-3

Quarterly Progress Report for January through March 2001

Date Time Hour Vacuum VOCs Conc. Total TCE Total			Elapsed	FI	DW		Total	TCE	[	ed VOC al Rates	l	ulative Remova	
3/16/00   9:57   5.6   0.41   0.37   35   31   25   0.0047   0.0054   0   0	Date	Time	Meter	(acfm)	(scfm)		VOCs by PID	Conc. by Lab	1	VOCs	l	VOCs	Notes
System Startup on 3/16/00 at 16:00   3/17/00   7:00   20.3   0.98   0.89   37   6.1   -   3/18/00   6:30   44.7   0.98   0.89   38   8.3   -	репримененти и положения в	Static va	apor samp	le collec	cted on	3/1 <b>6</b> /00.	Proposition of the Control of the Co	emone.				444999999	######################################
3/17/00 7:00 20.3 0.98 0.89 37 6.1 - 3/18/00 6:30 44.7 0.98 0.89 38 8.3 -  System shut down on 3/18/00 at 9:40. System restarted on 3/19/00 at 6:30.  3/19/00 6:30 47.9 0.98 0.89 38 45 - 3/20/00 6:30 72.2 0.98 0.88 43 7.4 - 3/22/00 7:30 120.5 0.95 0.91 15 10 - 3/32/000 11:00 316.0 0.76 0.69 38 29 - 4/6/00 11:00 316.0 0.76 0.69 38 29 - 4/6/00 11:00 483.0 1.6 1.1 125 25 - 4/4/3/00 8:00 648.0 2.1 1.3 150 22 - 4/20/00 7:30 8150 1.7 1.1 145 6.8 - 5/11/00 6:30 1,318.0 1.6 0.98 150 2.8 - 5/11/00 6:30 1,318.0 1.6 0.98 150 2.8 - 5/11/00 6:30 1,318.0 1.6 0.98 150 9.0 - 5/25/00 6:30 1,654.0 1.6 0.98 150 9.0 - 5/25/00 6:30 1,654.0 1.6 0.99 150 4.2 - 6/11/00 6:30 1,822.0 1.5 0.95 150 7.5 - 6/11/00 6:30 1,822.0 1.5 0.95 150 7.5 - 6/11/00 6:30 1,822.0 1.5 0.95 150 7.5 - 5/18/00 7:00 1,990.0 1.4 0.88 155 5.2 - 6/15/00 7:30 2,158.0 1.4 0.90 150 4.9 -  System shut down on 6/21/00 at 17:30. Static vapor sample collected on 7/6/00.  7/13/00 12:00 2,485 2.3 1.5 130 7.3 7.4 0.0057 0.0095 0.50  System restarted on 7/6/00 at 10:00.  7/13/00 12:00 2,485 2.3 1.5 145 3.5 - 7/20/00 7:30 2,648 2.2 1.4 150 4.1 -  System shut down on 7/26/00 at 6:30. System restarted on 7/27/00 at 6:00.  7/27/00 6:00 2,791 1.9 1.3 140 5.1 -  System shut down on 7/26/00 at 6:30. System restarted on 7/27/00 at 6:00.	3/16/00	9:57	5.6	0.41	0.37	35	31	25	0.0047	0.0054	0	0	
3/18/00 6:30 44.7 0.98 0.89 38 8.3 -  System shut dow on 3/18/00 at 9:40. System restarted on 3/19/00 at 6:30.  3/19/00 6:30 47.9 0.98 0.89 38 45 -		System	Startup or	n 3/16/00	at 16:0	0.							
3/18/00 6:30 44.7 0.98 0.89 38 8.3 -  System shut dow → on 3/18/00 at 9:40. System restarted on 3/19/00 at 6:30.  3/19/00 6:30 47.9 0.98 0.89 38 45 -	3/17/00	7:00	20.3	0.98	0.89	37	6.1	_					
System shut down on 3/18/00 at 9:40. System restarted on 3/19/00 at 6:30.	1					1		_					
3/19/00 6:30 47.9 0.98 0.89 38 45 - 3/20/00 6:30 72.2 0.98 0.88 43 7.4 - 3/21/00 7:00 96.3 1.0 0.85 60 11 - 3/22/00 7:30 120.5 0.95 0.91 15 10 - 3/22/00 7:30 120.5 0.95 0.91 15 10 - 3/22/00 7:30 120.5 0.95 0.91 15 10 - 4/6/00 11:00 316.0 0.76 0.69 38 29 - 4/6/00 11:00 483.0 1.6 1.1 125 25 - 4/13/00 8:00 648.0 2.1 1.3 150 22 - 4/20/00 7:30 815.0 1.7 1.1 145 6.8 - 4/27/00 7:00 983.0 1.2 0.78 150 4.3 - 5/14/00 8:30 1,152.0 1.6 0.98 150 2.8 - 5/14/00 6:30 1,318.0 1.6 1.0 150 2.2 - 5/18/00 7:00 1,486.0 1.6 0.98 150 9.0 - 5/25/00 6:30 1,654.0 1.6 0.98 150 9.0 - 6/6/00 7:00 1,990.0 1.4 0.88 155 5.2 - 6/15/00 7:30 2,158.0 1.4 0.90 150 4.9 -  System shut down on 6/21/00 at 17:30. Static vapor sample collected on 7/6/00.  7/6/00 8:46 2,312 2.3 1.5 130 7.3 7.4 0.0057 0.0095  System restarted on 7/6/00 at 10:00.  7/13/00 12:00 2,485 2.3 1.5 145 3.5 - 7/20/00 7:30 2,648 2.2 1.4 150 4.1 -  System shut down on 7/26/00 at 6:30. System restarted on 7/27/00 at 6:00.  7/27/00 6:00 2,791 1.9 1.3 140 5.1 - System shut down on 7/26/00 at 6:30. System restarted on 7/27/00 at 6:00.			,			•	•	rted on 3/	' /19/00 at 6:	30.			
3/20/00   6:30   72.2   0.98   0.88   43   7.4   -	3/19/00	_						_					
3/21/00	1		i			1		-					•
3/22/00 7:30 120.5 0.95 0.91 15 10 - 3/30/00 11:00 316.0 0.76 0.69 38 29 - 4/6/00 11:00 483.0 1.6 1.1 125 25 - 4/13/00 8:00 648.0 2.1 1.3 150 22 - 4/20/00 7:30 815.0 1.7 1.1 145 6.8 - 4/27/00 7:00 983.0 1.2 0.78 150 4.3 - 5/4/00 8:30 1,152.0 1.6 0.98 150 2.8 - 5/11/00 6:30 1,318.0 1.6 1.0 150 2.2 - 1.6 0.98 150 9.0 - 5/25/00 6:30 1,654.0 1.6 0.98 150 9.0 - 5/25/00 6:30 1,822.0 1.5 0.95 150 7.5 - 6/11/00 6:30 1,822.0 1.5 0.95 150 7.5 - 6/11/00 7:00 1,990.0 1.4 0.88 155 5.2 - 6/15/00 7:30 2,158.0 1.4 0.90 150 4.9 -  System shut down on 6/21/00 at 17:30. Static vapor sample collected on 7/6/00.  7/6/00 8:46 2,312 2.3 1.5 130 7.3 7.4 0.0057 0.0095 0.50 0.71  System restarted on 7/6/00 at 10:00.  7/13/00 12:00 2,485 2.3 1.5 145 3.5 - 7/20/00 7:30 2,648 2.2 1.4 150 4.1 -  System shut down on 7/26/00 at 6:30. System restarted on 7/27/00 at 6:00.  7/27/00 6:00 2,791 1.9 1.3 140 5.1 - 8/3/00 8:00 2,961 1.9 1.3 140 2.2 - 8/8/00 14:30 2,961 1.9 1.3 140 2.2 -						Į	l	_					
3/30/00 11:00 316.0 0.76 0.69 38 29 - 4/6/00 11:00 483.0 1.6 1.1 125 25 - 4/13/00 8:00 648.0 2.1 1.3 150 22 - 4/13/00 7:30 815.0 1.7 1.1 145 6.8 - 4/13/100 7:00 983.0 1.2 0.78 150 4.3 - 5/4/00 8:30 1,152.0 1.6 0.98 150 2.8 - 5/11/00 6:30 1,318.0 1.6 1.0 150 2.2 - 5/18/00 7:00 1,486.0 1.6 0.98 150 9.0 - 1.6 0.98 150 9.0 - 1.6 0.98 150 9.0 - 1.6 0.98 150 9.0 - 1.6 0.98 150 9.0 - 1.6 0.98 150 9.0 - 1.6 0.98 150 9.0 - 1.6 0.98 150 9.0 - 1.6 0.98 150 9.0 - 1.6 0.98 150 9.0 - 1.6 0.98 150 9.0 - 1.6 0.98 150 9.0 - 1.6 0.98 150 9.0 - 1.6 0.98 150 9.0 - 1.6 0.98 150 9.0 - 1.6 0.98 150 9.0 - 1.6 0.98 150 9.0 - 1.6 0.98 150 9.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1	į.					1	1	-					
4/6/00	I					1	ı	-	Marie Control				
4/13/00       8:00       648.0       2.1       1.3       150       22       -       4/20/00       7:30       815.0       1.7       1.1       145       6.8       -       4/27/00       7:00       983.0       1.2       0.78       150       4.3       -       5/4/00       8:30       1,152.0       1.6       0.98       150       2.8       -       5/5/10/00       5/11/00       6:30       1,318.0       1.6       1.0       150       2.2       -       -       5/11/00       6:30       1,318.0       1.6       1.0       150       2.2       - <td>1</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>-</td> <td></td> <td></td> <td></td> <td></td> <td></td>	1							-					
4/27/00       7:00       983.0       1.2       0.78       150       4.3       -         5/4/00       8:30       1,152.0       1.6       0.98       150       2.8       -         5/11/00       6:30       1,318.0       1.6       1.0       150       2.2       -         5/18/00       7:00       1,486.0       1.6       0.98       150       9.0       -         5/25/00       6:30       1,654.0       1.6       0.99       150       4.2       -         6/1/00       6:30       1,822.0       1.5       0.95       150       7.5       -         6/8/00       7:00       1,990.0       1.4       0.88       155       5.2       -         6/15/00       7:30       2,158.0       1.4       0.90       150       4.9       -         System shut down on 6/21/00 at 17:30. Static vapor sample collected on 7/6/00.         7/6/00       8:46       2,312       2.3       1.5       130       7.3       7.4       0.0057       0.0095       0.50       0.71         System restarted on 7/6/00 at 6:30. System restarted on 7/27/00 at 6:00.         7/27/00       6:00       2,791	4/13/00	8:00	648.0	2.1		150	22	-					
5/4/00	4/20/00	7:30	815.0	1.7	1.1	145	6.8	-					
5/11/00	4/27/00	7:00	983.0	1.2	0.78	150	4.3	-					
5/18/00 7:00 1,486.0 1.6 0.98 150 9.0 - 5/25/00 6:30 1,654.0 1.6 0.99 150 4.2 - 6/1/00 6:30 1,822.0 1.5 0.95 150 7.5 - 6/8/00 7:00 1,990.0 1.4 0.88 155 5.2 - 6/15/00 7:30 2,158.0 1.4 0.90 150 4.9 -  System shut down on 6/21/00 at 17:30. Static vapor sample collected on 7/6/00.  7/6/00 8:46 2,312 2.3 1.5 130 7.3 7.4 0.0057 0.0095 0.50 0.71  System restarted on 7/6/00 at 10:00.  7/13/00 12:00 2,485 2.3 1.5 145 3.5 - 7/20/00 7:30 2,648 2.2 1.4 150 4.1 -  System shut down on 7/26/00 at 6:30. System restarted on 7/27/00 at 6:00.  7/27/00 6:00 2,791 1.9 1.3 140 5.1 - 8/3/00 8:00 2,961 1.9 1.2 140 2.2 - 8/8/00 14:30 2,961 1.9 1.3 140 2.3 -	5/4/00	8:30	1,152.0	1.6	0.98	150	2.8	-					
1.6	5/11/00	6:30	1,318.0	1.6	1.0	150	2.2	-					
5/25/00 6:30 1,654.0 1.6 0.99 150 4.2 - 6/1/00 6:30 1,822.0 1.5 0.95 150 7.5 - 6/8/00 7:00 1,990.0 1.4 0.88 155 5.2 - 6/15/00 7:30 2,158.0 1.4 0.90 150 4.9 -  System shut down on 6/21/00 at 17:30. Static vapor sample collected on 7/6/00.  7/6/00 8:46 2,312 2.3 1.5 130 7.3 7.4 0.0057 0.0095  System restarted on 7/6/00 at 10:00.  7/13/00 12:00 2,485 2.3 1.5 145 3.5 - 7/20/00 7:30 2,648 2.2 1.4 150 4.1 -  System shut down on 7/26/00 at 6:30. System restarted on 7/27/00 at 6:00.  7/27/00 6:00 2,791 1.9 1.3 140 5.1 - 8/3/00 8:00 2,961 1.9 1.2 140 2.2 - 8/8/8/00 14:30 2,961 1.9 1.3 140 2.3 -	5/18/00	7:00	1,486.0	1.6	0.98	150	9.0	-					
6/1/00 6:30 1,822.0 1.5 0.95 150 7.5 - 6/8/00 7:00 1,990.0 1.4 0.88 155 5.2 - 6/15/00 7:30 2,158.0 1.4 0.90 150 4.9 -  System shut down on 6/21/00 at 17:30. Static vapor sample collected on 7/6/00.  7/6/00 8:46 2,312 2.3 1.5 130 7.3 7.4 0.0057 0.0095 0.50 0.71  System restarted on 7/6/00 at 10:00.  7/13/00 12:00 2,485 2.3 1.5 145 3.5 - 7/20/00 7:30 2,648 2.2 1.4 150 4.1 -  System shut down on 7/26/00 at 6:30. System restarted on 7/27/00 at 6:00.  7/27/00 6:00 2,791 1.9 1.3 140 5.1 - 8/3/00 8:00 2,961 1.9 1.2 140 2.2 - 8/8/8/00 14:30 2,961 1.9 1.3 140 2.3 -				1.6	0.98	150	9.0	-					
6/8/00 7:00 1,990.0 1.4 0.88 155 5.2 - 6/15/00 7:30 2,158.0 1.4 0.90 150 4.9 -  System shut down on 6/21/00 at 17:30. Static vapor sample collected on 7/6/00.  7/6/00 8:46 2,312 2.3 1.5 130 7.3 7.4 0.0057 0.0095  System restarted on 7/6/00 at 10:00.  7/13/00 12:00 2,485 2.3 1.5 145 3.5 - 7/20/00 7:30 2,648 2.2 1.4 150 4.1 -  System shut down on 7/26/00 at 6:30. System restarted on 7/27/00 at 6:00.  7/27/00 6:00 2,791 1.9 1.3 140 5.1 - 8/3/00 8:00 2,961 1.9 1.2 140 2.2 - 8/8/8/00 14:30 2,961 1.9 1.3 140 2.3 -	5/25/00	6:30	1,654.0	1.6	0.99	150	4.2	-					
6/15/00 7:30 2,158.0 1.4 0.90 150 4.9 -  System shut down on 6/21/00 at 17:30. Static vapor sample collected on 7/6/00.  7/6/00 8:46 2,312 2.3 1.5 130 7.3 7.4 0.0057 0.0095 0.50 0.71  System restarted on 7/6/00 at 10:00.  7/13/00 12:00 2,485 2.3 1.5 145 3.5 -  7/20/00 7:30 2,648 2.2 1.4 150 4.1 -  System shut down on 7/26/00 at 6:30. System restarted on 7/27/00 at 6:00.  7/27/00 6:00 2,791 1.9 1.3 140 5.1 -  8/3/00 8:00 2,961 1.9 1.2 140 2.2 -  8/8/8/00 14:30 2,961 1.9 1.3 140 2.3 -	6/1/00		1,822.0	1.5	0.95	150		-					
System shut down on 6/21/00 at 17:30. Static vapor sample collected on 7/6/00.  7/6/00 8:46 2,312 2.3 1.5 130 7.3 7.4 0.0057 0.0095 0.50 0.71  System restarted on 7/6/00 at 10:00.  7/13/00 12:00 2,485 2.3 1.5 145 3.5 -  7/20/00 7:30 2,648 2.2 1.4 150 4.1 -  System shut down on 7/26/00 at 6:30. System restarted on 7/27/00 at 6:00.  7/27/00 6:00 2,791 1.9 1.3 140 5.1 -  8/3/00 8:00 2,961 1.9 1.2 140 2.2 -  8/8/6/00 14:30 2,961 1.9 1.3 140 2.3 -			· ·			3		-					
7/6/00 8:46 2,312 2.3 1.5 130 7.3 7.4 0.0057 0.0095 0.50 0.71  System restarted on 7/6/00 at 10:00.  7/13/00 12:00 2,485 2.3 1.5 145 3.5 -  7/20/00 7:30 2,648 2.2 1.4 150 4.1 -  System shut down on 7/26/00 at 6:30. System restarted on 7/27/00 at 6:00.  7/27/00 6:00 2,791 1.9 1.3 140 5.1 -  8/3/00 8:00 2,961 1.9 1.2 140 2.2 -  8/8/00 14:30 2,961 1.9 1.3 140 2.3 -	6/15/00		,			• .	i .	-					
System restarted on 7/6/00 at 10:00.         7/13/00       12:00       2,485       2.3       1.5       145       3.5       -         7/20/00       7:30       2,648       2.2       1.4       150       4.1       -         System shut down on 7/26/00 at 6:30. System restarted on 7/27/00 at 6:00.         7/27/00       6:00       2,791       1.9       1.3       140       5.1       -         8/3/00       8:00       2,961       1.9       1.2       140       2.2       -         8/8/00       14:30       2,961       1.9       1.3       140       2.3       -		System	shut dowr	n on 6/2	1/00 at 1	7:30. Sta	tic vapor	sample o	collected o	n 7/6/00.			
7/13/00 12:00 2,485 2.3 1.5 145 3.5 - 7/20/00 7:30 2,648 2.2 1.4 150 4.1 -  System shut down on 7/26/00 at 6:30. System restarted on 7/27/00 at 6:00.  7/27/00 6:00 2,791 1.9 1.3 140 5.1 - 8/3/00 8:00 2,961 1.9 1.2 140 2.2 - 8/8/00 14:30 2,961 1.9 1.3 140 2.3 -	7/6/00	8:46	2,312	2.3	1.5	130	7.3	7.4	0.0057	0.0095	0.50	0.71	4A
7/20/00 7:30 2,648 2.2 1.4 150 4.1 -  System shut down on 7/26/00 at 6:30. System restarted on 7/27/00 at 6:00.  7/27/00 6:00 2,791 1.9 1.3 140 5.1 -  8/3/00 8:00 2,961 1.9 1.2 140 2.2 -  8/8/00 14:30 2,961 1.9 1.3 140 2.3 -	PPRESENTATION OF THE PRESENTATION OF THE PRESE	System	restarted e	on 7/6/0	0 at 10:0	0.							
7/20/00 7:30 2,648 2.2 1.4 150 4.1 -  System shut down on 7/26/00 at 6:30. System restarted on 7/27/00 at 6:00.  7/27/00 6:00 2,791 1.9 1.3 140 5.1 -  8/3/00 8:00 2,961 1.9 1.2 140 2.2 -  8/8/00 14:30 2,961 1.9 1.3 140 2.3 -	7/13/00	12:00	2,485	2.3	1.5	145	3.5	-					
System shut down on 7/26/00 at 6:30. System restarted on 7/27/00 at 6:00.         7/27/00       6:00       2,791       1.9       1.3       140       5.1       -         8/3/00       8:00       2,961       1.9       1.2       140       2.2       -         8/8/00       14:30       2,961       1.9       1.3       140       2.3       -	7/20/00							-			POD-BILLOON POD-BI		
7/27/00     6:00     2,791     1.9     1.3     140     5.1     -       8/3/00     8:00     2,961     1.9     1.2     140     2.2     -       8/8/00     14:30     2,961     1.9     1.3     140     2.3     -			- 1				,	rted on 7/	/27/00 at 6:	00.			
8/3/00 8:00 2,961 1.9 1.2 140 2.2 - 8/8/00 14:30 2,961 1.9 1.3 140 2.3 -	7/27/00	=					1		1	-			
8/8/00 14:30 2,961 1.9 1.3 140 2.3 -			-			4		_					
			-			1 I		-					
	<b>,</b>			1		1		i arted on !	: 8/21/00 at 1	10:30.			
8/24/00 12:30 3,326 2.0 1.3 140 1.9 -	\$ <i>!</i> 2#!00	-							Primeriw Crack I	t nur h fuir fuir x			

#### **TABLE 4d**

# Soil Vapor Extraction Data: Extraction Well SVE-3

Quarterly Progress Report for January through March 2001

7		Elapsed	FI	ow				i .	ted VOC	l	ulative	
		Time on				Total	TCE	Remov	al Rates		Remova	
Date	Time	Hour Meter (hrs)	(acfm)	(scfm)	Vacuum (in-wc)	VOCs by PID (ppmv)	Conc. by Lab (ppmv)	TCE (lb/day)	Total VOCs (lb/day)	TCE (lbs)	Total VQCs (lbs)	Notes
	System	shut dowi	on 8/30	0/00 at 1	3:30. Sys	tem rest	arted on a	8/31/00 at 9	9:00.			
8/31/00	9:00	3,471	1.4	1.0	120	2.6	-					
	System :	shut dow	n on 9/6/	00 at 15	:00. Syst	em resta	rted on 9/	7/00.				
9/7/00	10:30	3,621	1.4	1.0	125	1.2	4m					
9/14/00	9:00	3,788	1.5	1.0	140	1.5	2.5	0.0012	0.0028	0.71	1.1	4A
	System :	shut dowi	n on 9/1	4/00 for	rebound t	est. Stat	ic vapor	sample co	llected on	9/28/00.		
9/28/00	9:52	3,788	-	-	120	8.0	3.8	- ,	•	-	-	,
	System :	shut dowi	n on 9/2	8/00 at 1	2:00. Sys	tem rest	arted on 1	10/1/00 at <b>(</b>	5: <b>30</b> .			
10/1/00	6:30	3,791	-	•	-	-	-			of the first seasons		
	System :	shut dow	n on 10/	1/00 at 1	0:30. Sys	tem rest	arted on '	10/5/00 at 7	7:30.			
10/5/00	7:30	3,795	1.8	1.3	120	4.6	-					
10/12/00	8:00	3,964	1.9	1.3	120	5.6	-	,				
10/19/00	8:00	4,132	1.9	1.3	120	4.1	-					
10/26/00	8:00	4,301	1.9	1.3	115	4.1	**			WHITE STATE OF THE		
ı	•				. • • • • • • • • • • • • • • • • • • •		arted on '	11/2/00 at 8	3:00.			
11/2/00	8:00	4,422	i	4.7	140		-					
	-	shut dow	on 11/3	2/00 at 1			arted on '	11/9/00 at 7	7:30.			
11/9/00	7:30	4,433	1.9	1.3	140	25.2	-			MINISTER STATE OF THE STATE OF		
	System	shut dow	n on 11/9	9/00 at 1	5:30. Sys	tem rest	arted on 1	11/16/00 at	10:00.			
11/16/00	10:00	4,441	i	-	140	8.9	-					
11 C - CC	System	shut dow	1 on 11/	17/00 at	12:00. Sy	stem res	tarted on	11/23/00 a	t 7:30.			
11/23/00	7:30	4,443	-	-	140	11.9	-					
11/30/00	7:30	4,611	5.6	3.6	140	6.2	-					ļ
	System :		n on 12/	6/00 at 2		tem rest	arted on	12/7/00 at 8	3:00.			
12/7/00	8:00	4,768	-	-	140	14.4						
12/14/00	10:30	4,940	2.3	1.5	140	1,2	1.2	0.00089	0.0023	0.76	1.2	4A
	System	shut dow	1 on 12/	14/00 for	rebound	test.						
1/4/01	9:45	4,940	2.1	1.5	120	1.5	1.3	-	-	-	ne.	

#### TABLE 4d

### Soil Vapor Extraction Data: Extraction Well SVE-3

Quarterly Progress Report for January through March 2001

Jervis B. Webb Company of California, 5030 Firestone Boulevard, South Gate, California

		Elapsed		ow		Total	TCE		ed VOC al Rates		iulative Remova	
Date	Time	Time on Hour Meter (hrs)	(acfm)	(scfm)	Vacuum (in-wc)	Ī	Conc. by Lab (ppmv)	TCE (lb/day)	Total VOCs (lb/day)	TCE (lbs)	Total VOCs (lbs)	Notes
	System	shut dow	on 1/4	01. Sys	tem resta	rted on 2	/19/01 at	15:45.				
2/19/01	15:45	4,940	3.8	2.5	140	6.0	-					
2/22/01	17:00	5,016	3.4	2.2	140	6.4	-					
3/1/01	12:45	5,180	2.6	1.7	140	6.3	Mark.					
3/8/01	7:30	5,343	2.6	1.7	145	0.0	**					
3/15/01	13:00	5,516	2.6	1.7	145	0.5	-					
3/22/01	13:00	5,682	2.6	1.7	145	3.3	-	editority of the control				
3/29/01	14:30	5,854	2.7	1.7	140	8.3	-	***		-	-	

#### NOTES:

TCE = trichloroethene

acfm = actual cubic feet per minute

°F = degrees Fahrenheit

hrs = hours

in-wc = inches of water column

lb/day = pounds per day

lbs = pounds

PID = photoionization detector

ppmv = parts per million by volume

scfm = standard cubic feet per minute

tr = trace (concentration detected at less than reporting limit)

VOCs = volatile organic compounds

- = no measurement

< = not detected at indicated method detection limit</p>

- 1. PID calibrated with 100 ppmv of isobutylene.
- 2. Laboratory analyses were performed by Performance Analytical, Inc. in Simi Valley, California using EPA Method TO-14A.
- 3. Removal rates are calculated using analyte concentrations from laboratory analyses and the measured flow rate (converted from acfm to sofm using the measured vacuum).
- 4. Cumulative mass removal amounts are calculated as follows:
  - A: Mass removal calculated using an average of the previous and current mass removal rates.
- 5. On days for which two flow and vacuum readings are provided, the values indicate initial and final readings during the site visit.
- 6. Aithough not shown on this table, mass removal rates were calculated for each VOC detected in the samples collected from well SVE-3. The total VOC mass removal rate presented in this table is the sum of the mass removal rates calculated for each VOC that was detected.
- 7. Extraction well SVE-3 is screened in the shallow vadose zone from 19 to 25 feet below ground surface.

# TABLE 4e

## Soil Vapor Extraction Data: Extraction Well SVE-D1

Quarterly Progress Report for January through March 2001

			FI	ow	***************************************				ted VOC		ulative	
SERVICE CONTRACTOR CON		Elapsed		,		Total	TCE	Remov	al Rates		Remova	1
Date	Time	Time on Hour Meter (hrs)	(acfrn)	(scfm)	Vacuum (in-wc)	VOCs by PID (ppmv)	Conc. by Lab (ppmv)	TCE (lb/day)	Total VOCs (lb/day)	TCE (lbs)	Total VOCs (lbs)	Notes
	Static va	ipor samp	le colle	cted on	<b>3/16</b> /00.		**************************************		The state of the s	***		
3/16/00	8:57	5.6	3.7	3.6	6.0	1,580	1,000	1.8	1. <del>9</del>	0	o	
	System	startup or	1 3/16/00	at 16:0	o.							
3/17/00	7:00	20.3	4.6	4.5	10	92	-					
3/18/00	6:30	44.7	5.3	5.2	10	131						
	System	shut dow	n on 3/1	8/00 at 9	i:40. Syst	em resta	rted on 3;	/ /19/00 at 6:	:30.			
3/19/00	6:30	48	0.0	0.0	0.0	30	0					
3/20/00	6:30	72	5,8	5.7	9.0	164	Ď					
3/21/00	7:00	96	2.6	2.6	7.0	560	0					
3/22/00	7:30	121	8.9	8.6	15	70	440	1.9	2.0	8.8	9.1	4A
3/30/00	11:00	316	24	22	38	36	0					
4/6/00	11:00	483	25	17	125	30	0					
4/13/00	8:00	648	33	21	150	33	25	0.26	0.28	32	34	4A
4/20/00	7:30	815	28	18	145	28	0					
4/27/00	7:00	983	18	16	40	25	0					
5/4/00	8:30	1,152	16	10	135	20	0					
5/11/00	6:30	1,318	13	9.7	95	13	0					
5/18/00	7:00	1,486	20	14	120	37	8.6	0.061	0.070	38	40	4A
			26	17	150	37	-	0.071	0.081	-	-	
5/25/00	6:30	1,654	18	11	150	16	-					
6/1/00	6:30	1,822	16	10	150	31	-					
6/8/00	7:00	1,990	21	13	155	31	-					
6/15/00	7:30	2,158	21	13	150	31						
						=		collected o	n 7/6/00.			
7/ <del>6</del> /00	9:34	2,312	0	0	0	30	92	ma.	-	-	-	
	System	restarted	on 7/6/0	0 at 10:0	00.							
7/13/00	12:00	2,485	34	22	145	37	5.1	0.056	0.25	40	47	4A
7/20/00	7:30	2,648	32	20	150	27	-					
	System	shut dow	on 7/2	6/00 at 6	:30. Syst	em resta	rted on 7/	27/00 at 6:	:00.			
7/27/00	6:00	2,791	26	17	140	9.4						
8/3/00	8:00	2,961	26	17	140	1.5	-					
8/8/00	14:30	3,086	26	17	140	1.8						
	System	shut dow	1 on 8/1	5/00 at 1	1:30. Sys	stem rest	arted on a	8/21/00 at 1	10:30.			

### **TABLE 4e**

### Soil Vapor Extraction Data: Extraction Well SVE-D1

Quarterly Progress Report for January through March 2001

		P=1	FI	DW DW			,	i	ed VOC	1	ulative	
		Elapsed		_ **		Total	TCE	Remov	al Rates		Remova	<u> </u>
Date	Time	Time on Hour Meter (hrs)	(acfm)	(scfm)	Vacuum (in-wc)	VOCs by PID (ppmv)	Conc. by Lab (ppmv)	TCE (lb/day)	Total VOCs (lb/day)	TCE (lbs)	Total VOCs (lbs)	Nates
8/24/00	12:30	3,226	27	18	140	17	_		2022			
	System :	shut dowr	1 on 8/30	0/00 at 1	3:30. Sys	stem rest	arted on	8/31/00 at 9	9:00.			
8/31/00	9:00	3,471	21	15	120	8.9	-	- Arrivante		-		
	System :	shut dow	on 9/6/	'00 at 15	:00. Syst	em resta	rted on 9	/7/00.				
9/7/00	10:30	3,621	22	15	125	5.8	-	MANUFACA		with the first of		
9/14/00	9:00	3,788	20	13	140	24	4.0	0.026	0.23	43	60	4A
	System :	shut dowr	on 9/1	4/00 for	rebound t	test. Stat	ic vapor	sample co	llected on	9/28/00	•	
9/28/00	10:25	3,788	52	36	120	62	120		-	-	-	
	System :	shut dow	on 9/2	8/00 at 1	2:00. Sy	stem rest	arted on	10/1/00 at (	5:30.			
10/1/00	6:30	3,791	-	*	-	+	_					
	System :	shut dow	on 10/	1/00 at 1	0:30. Sys	stem rest	arted on	10/5/00 at 1	7:30.			
10/5/00	7:30	3,795	29	21	120	41	-	**************************************				
10/12/00	8:00	3,964	28	20	120	72	~			E		
10/19/00	8:00	4,132	19	14	120	6.2	-			and the second s		
10/26/00	8:00	4,301	20	14	115	5.8	2.4	0.017	0.081	43	63	4A
	System :			31/00 at	9:20. Sys	stem rest	arted on '	11/2/00 at 8	3:00.			
11/2/00	8:00	4,422	22	15	140	1.5	-	and the same of th				
	System	shut dow	on 11/2	2/00 at 1	9:00. Sys	stem rest	arted on	11/9/00 at 1	7:30.			
11/9/00	7:30	4,433	22	15	140	4.9	-					
-	System :	shut dowi	on 11/9	9/00 at 1	5:30. Sys	stem rest	arted on	11/16/00 at	10:00.			
11/16/00	10:00	4,441	24	15	140	38	-					
	System :	shut dowi	on 11/	17/00 at	12:00. Sy	ystem res	tarted on	11/23/00 (	at 7:30.			
11/23/00	7:30	4,443	24	16	140	29	-			-		
11/30/00		4,611	•			•	•	<b>В</b> ызмымие		THE PERSONNEL PROPERTY.		
***************************************	•		on 12/	6/00 at 2	1:00. Sys	stem rest	arted on	12/7/00 at t	3:00.			
12/7/00	8:00	4,768	-		140	12	•	NAME OF THE PROPERTY OF THE PR				
12/14/00	10:30	4,940	16	<b>1</b> 1	140	3.1	2.7	0.014	0.025	44	64	4A
	System :	shut dow	on 12/	14/00 fo	r rebound	l test.						
1/4/01	10:48	4,940	74	52	120	43	41	-	***	-	*	

#### **TABLE 4e**

### Soil Vapor Extraction Data: Extraction Well SVE-D1

Quarterly Progress Report for January through March 2001

Jervis B. Webb Company of California, 5030 Firestone Boulevard, South Gate, California

		Elapsed	Flo	DW		Total	TCE		ed VOC al Rates		ulative Remova	
Date	Time	Time on Hour Meter (hrs)	(acfm)	(scfm)	Vacuum (in-wc)		Conc. by Lab (ppmv)	TCE (lb/day)	Total VOCs (lb/day)	TCE (lbs)	Total VOCs (lbs)	Notes
	System	shut dowr	on 1/4/	01. Sys	tem resta	irted on 2	2/19/01 at	15:45.			······································	
2/19/01	15:45	4,940	23	15	140	43	-					
2/22/01	17:00	5,016	24	15	140	37	-			Annual Control		
3/1/01	12:45	5,180	24	15	140	81	***	OC 1000000000000000000000000000000000000				
3/8/01	7:30	5,343	23	15	145	103	-	- No				
3/15/01	13:00	5,516	22	14	145	9.4	-					
3/22/01	13:00	5,682	21	14	145	12	ana.					
3/29/01	14:30	5,854	21	14	130	10	æ	*	Says.		**	

#### NOTES:

TCE = trichloroethene

acfm = actual cubic feet per minute

°F = degrees Fahrenheit

hrs = hours

in-wc = inches of water column

lb/day = pounds per day

lbs = pounds

PID = photoionization detector

ppmv = parts per million by volume

scfm = standard cubic feet per minute

tr = trace (concentration detected at less than reporting limit)

VOCs = volatile organic compounds

- = no measurement

<= not detected at indicated method detection limit

- 1. PID calibrated with 100 ppmv of isobutylene.
- 2. Laboratory analyses were performed by Performance Analytical, Inc. in Simi Valley, California using EPA Method TO-14A.
- 3. Removal rates are calculated using analyte concentrations from laboratory analyses and the measured flow rate (converted from acfm to scfm using the measured vacuum).
- 4. Cumulative mass removal amounts are calculated as follows:
  - A: Mass removal catculated using an average of the previous and current mass removal rates.
- On days for which two flow and vacuum readings are provided, the values indicate initial and final readings during the site visit.
- 6. Although not shown on this table, mass removal rates were calculated for each VOC detected in the samples collected from well SVE-D1. The total VOC mass removal rate presented in this table is the sum of the mass removal rates calculated for each VOC that was detected.
- 7. Extraction well SVE-D1 is screened in the shallow vadose zone from 30 to 40 feet below ground surface.

#### **TABLE 4f**

# Soil Vapor Extraction Data: Monitoring/Extraction Well VMP-D1

Quarterly Progress Report for January through March 2001

		Elapsed	Flo	ow		Total	TCE	l	ed VOC al Rates		ulative Remova	
Date	Time	Time on Hour Meter (hrs)	(acfm)	(scfm)	Vacuum (in-wc)	VOCs by PID (ppmv)	Conc. by Lab (ppmv)	TCE (lb/day)	Total VOCs (lb/day)	TCE (lbs)	Total VOCs (lbs)	Notes
	Static va	por samp	le colle	cted on	3/16/00.							
3/16/00	10:32	5.6	0	0	0	282	460					
	System	startup or	1 3/16/00	at 16:0	0 with VM	P-D1 use	ed as a m	onitoring v	vell.			
4/6/00	11:00	483	0	0	0	3.5	_					
4/13/00	8:00	648	0	0	0	23	-					
	Systèm	shut dow	n on 6/2	1/00 at 1	7:30. Sta	tic vapor	sample	collected o	n 7/6/00.		•	
7/6/00	8:57	2,312	35	24	130	30	9.4	0.11	0.12	0	0	
	System	restarted	on 7/6/0	0 at 10:0	00 with VM	/IP-D1 op	erating a	s an extrac	ction well.			
7/13/00	12:00	2,485	33	21	145	3.6	0					
7/20/00	7:30	2,648	34	22	150	3.2	-					
7/27/00	6:00	2,791	26	17	140	9.4	-					
8/3/00	8:00	2,961	25	16	140	1.5	-					
8/8/00	14:30	3,086	24	16	140	1.6	-					
	-	shut dow					arted on	8/21/00 at	10:30.			
8/24/00	12:30	3,326	22	15	140	2.1	-					
	System	shut dow	n on 8/30	0/00 at 1	3:30. Sys	stem rest	arted on	8/31/00 at 9	9:00.			
8/31/00	9:00	3,471	19	14	120	0.9	~					
	System	shut dow	n on 9/6/	00 at 15	:00. Syst	em resta	rted on 9	/7/00.				
9/7/00	10:30	3,621	20	14	125	0.2	-					
9/14/00	9:00	3,788	20	-	140	1.2	1.4	0.0090	0.012	3.7	4.2	4A
	System	shut dow	n on 9/1	4/00 for	rebound	test. Stat	tic vapor	sample co	llected on	9/28/00.		
9/28/00	10:08	3,788	59	41	120	6.3	8.6	-	-	-	-	
	System	shut dow	n on 9/2	3/00 at 1	2:00. Sys	stem rest	arted on	10/1/00 at	6:30.			
10/1/00	6:30	3,791	_	-	-	-	-					
	System	shut dow	n on 10/	1/00 at 1	0:30. Sys	stem rest	arted on	10/5/00 at 1	7:30.			
10/5/00	7:30	3,795	25	18	120	8.4	-					
10/12/00	8:00	3,964	24	17	120	6.7	-					
10/19/00	8:00	4,132	25	17	120	9.4	-					
10/26/00	8:00	4,301	22	16	115	24	-					
	System	shut dow	n on 10/:	31/00 at	9:20. Sys	stem rest	arted on	11/2/00 at	8:00.			

#### **TABLE 4f**

# Soil Vapor Extraction Data: Monitoring/Extraction Well VMP-D1

Quarterly Progress Report for January through March 2001

Jervis B. Webb Company of California, 5030 Firestone Boulevard, South Gate, California

7777		Elapsed	FI	DW		Total	TCE	1	ted VOC al Rates	1	ulative Remova	
Date	Time	Time on Hour Meter (hrs)	(acfm)	(scfm)	Vacuum (i⊓-wc)	VOCs by PID (ppmv)	Conc. by Lab (ppmv)	TCE (lb/day)	Total VOCs (lb/day)	TCE (lbs)	Total VOCs (lbs)	Notes
11/2/00	8:00	4,422	26	17	140	0	-					FFF MANOOOD MANAGEMENT
	System :	shut dow	n on 11/2	2/00 at 1	9:00. Sys	stem rest	arted on	11/9/00 at	7:30.			
11/9/00	7:30	4,433	-	~	140	59	-	WANTED THE PROPERTY OF THE PRO				
	System :	shut dow	n <b>on 11</b> /9	9/00 at 1	5:30. Sys	stem rest	arted on	11/16/00 at	10:00.			
11/16/00	10:00	4,441	64	42	140	8.6	-			THE STATE OF THE S		
	System :	shut dowi	n on 11/	17/00 at	12:00. S	stem res	started or	11/23/00	at 7:30.			
11/23/00	7:30	4,443	60	40	140	87.4	-					
11/30/00	7:30	4,611	39	26	140	27.9						
	System :	shut dowi	on 12/	5/00 at 2	1:00. Sys	stem rest	arted on	12/7/00 at	B:00.			
12/7/00	8:00	4,768	42	27	140	29.3	-					
12/14/00	10:30	4,940	15	10	140	0.3	0.95	0.0047	0.0065	4.0	4.6	4A
The state of the s	System :	shut dow	n on 12/	14/00 fo	r rebound	l test.						
1/4/01	9:57	4,940	76	53	120	0.6	1.6	·**		-	****	
	System :	shut dowi	n <b>on 1/4</b> /	01. Sys	tem resta	rted on 2	2/19/01 at	15:45.				
2/19/01	15:45	4,940	22	15	140	1.2	-					
2/22/01	17:00	5,016	23	15	140	0.0	-	AND				ı
3/1/01	12:45	5,180	18	12	140	0.0	-	nere annual market				
3/8/01	7:30	5,343	19	12	145	0.0	-		,	AND		
3/15/01	13:00	5,516 5,693	18	12 12	145	0.8	-					
3/22/01 3/29/01	13:00 14:30	5,682 5,854	19 19	12 13	145 140	0.2 0.6	_					

#### **TABLE 4f**

# Soil Vapor Extraction Data: Monitoring/Extraction Well VMP-D1

Quarterly Progress Report for January through March 2001

Jervis B. Webb Company of California, 5030 Firestone Boulevard, South Gate, California

Date		Elapsed		w		Total	TÇE	Į.	ed VOC al Rates		ulative Remova	
Date	Time	Time on Hour Meter (hrs)	(acfm)		Vacuum (in-wc)	VOCs by PID (ppmv)	Conc. by Lab (ppmv)	TCE (lb/day)	Total VOCs (lb/day)	TCE (lbs)	Total VOCs (lbs)	Notes

#### NOTES:

TCE = trichloroethene

acfm = actual cubic feet per minute

°F = degrees Fahrenheit

hrs = hours

in-wc = inches of water column

lb/day = pounds per day

lbs = pounds

PID = photoionization detector

ppmv = parts per million by volume

scfm = standard cubic feet per minute

tr = trace (concentration detected at less than reporting limit)

VOCs = volatile organic compounds

- = no measurement

< = not detected at indicated method detection limit

- 1. PID calibrated with 100 ppmv of isobutylene.
- 2. Laboratory analyses were performed by Performance Analytical, Iric. in Simi Valley, California using EPA Method TO-14A.
- 3. Removal rates are calculated using analyte concentrations from laboratory analyses and the measured flow rate (converted from acfm to sofm using the measured vacuum).
- 4. Cumulative mass removal amounts are calculated as follows:
  - A: Mass removal calculated using an average of the previous and current mass removal rates.
- 5. Well VMP-D1 was first used as an extraction well on 6 July 2000.
- 6. Although not shown on this table, mass removal rates were calculated for each VOC detected in the samples collected from well VMP-D1. The total VOC mass removal rate presented in this table is the sum of the mass removal rates calculated for each VOC that was detected.
- 7. Extraction well VMP-D1 is screened in the deep vadose zone from 30 to 40 feet below ground surface.

### **TABLE 4g**

# Soil Vapor Extraction Data: Monitoring/Extraction Well VMP-D2

Quarterly Progress Report for January through March 2001

The state of the s		Elapsed		)W		Total	TCE	d .	ed VOC al Rates	f .	ulative Remova	
Date	Time	Time on Hour Meter (hrs)	(acfm)	(scfm)	Vacuum (in-wc)	VOCs by PID (ppmv)	Conc. by Lab (ppmv)	TCE (lb/day)	Total VOCs (lb/day)	TCE (lbs)	Total VOCs (lbs)	Notes
~	Static va	por samp	le colle	cted on	3/16/00.			77700000	oniisan VV		Vanni	
3/16/00	10:50	5.6	0	0	0	76	39					
	System :	startup or	i 3/16/00	at 16:0	0 with VM	P-D2 use	d as a m	onitoring v	vell.			
4/6/00	11:00	483	0	0	l o 1	150	_	_				
4/13/00	8:00	648	0	0	0	27	-			4 leave		
	System :	shut dowr	n on 6/2	1/00 at 1	7:30. Sta	tic vapor	sample d	collected a	n 7/6/00.			
7/6/00	9:12	2,312	44	30	130	5.2	5.7	0.085	0.10	0	0	
	System	restarted	on 7/6/0	0 at 10:0	10 with VN	MP-D2 op	erating a	s an extrac	ction well.	The state of the s		
7/13/00	12:00	2,485	41	26	145	5.8	_			t the state of the		
7/20/00	7:30	2,648	42	27	150	3.8	-	Annal Anna				
7/27/00	6:00	2,791	21	14	140	8.7	-			u u u u u u u u u u u u u u u u u u u		
8/3/00	8:00	2,961	21	14	140	4.8						I
8/8/00	14:30	3,086	22	14	140	4.3	-					
	System	shut dowr	on 8/1	5/00 at 1	1:30. Sys	stem rest	arted on	8/21/00 at	10:30.			
8/24/00	12:30	3,326	26	17	140	8.8	-			en e		
	System :	shut dowi	n on 8/3	0/00 at 1	3:30. Sys	stem rest	arted on	8/31/00 at 9	9:00.			
8/31/00	9:00	3,471	18	13	120	1.5	-	9999				
	System :	shut dowr	n on 9/6/	00 at 15	:00. Syst	em resta	rted on 9.	/7/00.				
9/7/00	10:30	3,621	17	12	125	0.6	-					
9/14/00	9:00	<b>3</b> ,788	17	11	140	9.6	0.71	0.0040	0.038	2.8	4.4	4A
	System :	shut dowr	on 9/1	4/00 for	rebound 1	lest. Stal	tic vapor	sample co	llected on	9/28/00.		
9/28/00	9:35	3,788	42	29	125	39	9.3		er		-	
	System	shut dowi	n on 9/2	8/00 at 1	2:00. Sys	stem rest	arted on	10/1/00 at (	5:30.	The state of the s		
1	-	3,791			- 1							
1		•						; 10/5/00 at ī	7:30.			
10/5/00	7:30	3,795	23	16	120	24	_					
10/12/00	8:00	3,964	26	18	120	9.1	•••	THE STATE OF THE S				
10/19/00	8:00	4,132	25	18	120	10	_					
10/26/00	8:00	4,301	19	14	115	26	-					
			1 on 10/3	31/00 at	, ,	tem rest	arted on	' 11/2/00 at 8	B:00.	M. A.		
	J				·					<u> </u>		

### **TABLE 4g**

# Soil Vapor Extraction Data: Monitoring/Extraction Well VMP-D2

Quarterly Progress Report for January through March 2001

		Elapsed	Flo	w		Total	TCE	Ĭ.	ted VOC al Rates		ulative Remova	
Date	Time	Time on Hour Meter (hrs)	(acfm)	(scfm)	Vacuum (in-wc)	VOCs by PID (ppmv)	Conc. by Lab (ppmv)	TCE (lb/day)	Total VOCs (lb/day)	TCE (lbs)	Total VOCs (lbs)	Notes
11/2/00	8;00	4,422	23	15	140	0	_	уу тамандааны				about the same of
Held the Street was	System	shut dowr	on 11/	2/00 at 1	9:00. Sys	stem rest	arted on	11/9/00 at	7:30.			
11/9/00	7:30	4,433	-		140	14	-					
	System	shut dowr	n an 11/9	9/00 at 1	5:30. Sys	stem rest	arted on	11/16/00 at	t 10:00.			
11/16/00	10:00	4,441	-	-	140	15	-					
-	System	shut dowr	n on 11) <sup>,</sup>	17/00 at	12:00. Sy	ystem res	started on	11/23/00 ;	at 7:30.	-		
11/23/00	7:30	4,443	47	31	140	63	-					
11/30/00	7:30	4,611	28	18	140	45	~					
	System	shut dowr	on 12/0	6/00 at 2	1:00. Sys	stem rest	arted on	12/7/00 at	B:00.			
12/7/00	8:00	4,768	11	7.4	140	40	-					
12/14/00	10:30	4,940	18	12	140	14	1.3	0.0078	0.091	3.0	7.5	4A
	System	shut dowr	on 12/	14/00 fo	r rebound	l test.						
1/4/01	9:57	4,940	78	55	120	3.4	3.0	ini		-	1941	
	System	shut dowr	on 1/4/	01. Sys	tem resta	rted on 2	2/19/01 at	15:45.				
2/19/01	15:45	4,940	21	14	140	73.4	- 1					
2/22/01	17:00	5,016	21	14	140	81.9	-					
3/1/01	12:45	5,180	20	13	140	185.4	-			Wanted State of the State of th		
3/8/01	7:30	5,343	22	14	145	153.3	***	Payarentendring A				
3/15/01	13:00	5,516	24	15	145	5.2	-					
3/22/01	13:00	5,682	15	10	145	3.2	-			Av A		
3/29/01	14:30	5,854	19	13	140	2.6	<u> </u>				VIII	•••••

#### TABLE 4g

# Soil Vapor Extraction Data: Monitoring/Extraction Well VMP-D2

Quarterly Progress Report for January through March 2001

Jervis B. Webb Company of California, 5030 Firestone Boulevard, South Gate, California

Date Time		Elapsed		ow	A Paris Hall	Total	TCE	i	ted VOC al Rates		ulative l Remova	1
Date	Time	Hour Meter (hrs)	(acfm)	(scfm)	Vacuum (in-wc)	VOCs by PID (ppmv)	Conc. by Lab (ppmv)	TCE (lb/day)	Total VOCs (lb/day)	TCE (lbs)	Total VOCs (lbs)	Notes

#### NOTES:

TCE = trichloroethene

acfm = actual cubic feet per minute

°F = degrees Fahrenheit

hrs = hours

in-wc = inches of water column

lb/day = pounds per day

lbs = pounds

PID = photoionization detector

ppmv = parts per million by volume

scfm = standard cubic feet per minute

tr = trace (concentration detected at less than reporting limit)

VOCs = volatile organic compounds

- = no measurement

< = not detected at indicated method detection limit

- 1. PID calibrated with 100 ppmv of isobutylene.
- 2. Laboratory analyses were performed by Performance Analytical, Inc. in Simi Valley, California using EPA Method TO-14A.
- 3. Removal rates are calculated using analyte concentrations from laboratory analyses and the measured flow rate (converted from acfm to scfm using the measured vacuum).
- 4. Cumulative mass removal amounts are calculated as follows:
  - A: Mass removal calculated using an average of the previous and current mass removal rates.
- Well VMP-D1 was first used as an extraction well on 6 July 2000.
- 6. Although not shown on this table, mass removal rates were calculated for each VOC detected in the samples collected from well VMP-D2. The total VOC mass removal rate presented in this table is the sum of the mass removal rates calculated for each VOC that was detected.
- 7. Extraction well VMP-D2 is screened in the deep vadose zone from 30 to 40 feet below ground surface.

#### **TABLE 4h**

# Soil Vapor Extraction Data: Monitoring/Extraction Well VMP-1

Quarterly Progress Report for January through March 2001

	PANANAA TIIIII E MARAAAAAAAAAAAA	Elapsed	FI	ow		Total	TCE		ted VOC al Rates		ulative Remova	
Date	Time	Time on Hour Meter (hrs)	(acfm)	(scfm)	Vacuum (in-wc)	VOCs by PID (ppmv)	Conc. by Lab (ppmv)	TCE (lb/day)	Total VOCs (lb/day)	TCE (lbs)	Total VOCs (lbs)	Notes
	Static va	por samp	le colle	cted on	3/16/00.		, vonesti i					
3/16/00	11:35	5.6	0	0	0	65	29	•	-	-	1000	
	System :	startup or	3/16/00	at 16:0	0 with VM	P-1 used	as a moi	nitoring w	əll.			
4/6/00	11:00	483.0	0	0	0	6.4	-					
4/13/00	8:00	648.0	0	0	0	8.2	-					
	Static va	por samp	le colle	cted on	7/6/00.						•	
7/6/00	8:06	2,312.0	0	0	0	0.0	0.13	₩.	**	~	***	
	Vapor sa	imple col	ected o	n 9/14/0	0.							
9/14/00	11:08	3,788.0	0	0	0	0.5	0.29	-	Arr	-	-	
	Static va	por samp	le colle	cted on	9/28/00.							
9/28/00	8:51	3,788.0	0	0	0	1.3	0.47	•	-	-	•	
10/26/00	8:00	4,301.0	0	0	0	13						
	Static va	por samp	le colle	cted on	1/4/01.							
1/4/01	9:15	4,940.0	0	0	0	0.9	0.93	-	-	-	-	
	VMP-1 c	onverted	lo extra	ction we	II on 3/8/0	01.						
3/8/01	7:30	5,343.0	_	_	145	6,4	Selv					
2/22/01	17:00	5,016	23	15	140	0.0	-			4 3 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		
3/1/01	12:45	5,180	18	12	140	0.0						
3/8/01	7:30	5,343	19	12	145	0.0	-					
3/15/01	13:00	5,516	18	12	145	8.0	-					
3/22/01	13:00	5,682	19	12	145	0.2	-					
3/29/01	14:30	5,854	19	13	140	0.6	-					

#### TABLE 4h

# Soil Vapor Extraction Data: Monitoring/Extraction Well VMP-1

Quarterly Progress Report for January through March 2001

Jervis B. Webb Company of California, 5030 Firestone Boulevard, South Gate, California

Date		Elapsed				Total	TCE	1	Estimated VOC Removal Rates		Cumulative Mass Removal	
	Time	Hour Meter (hrs)	(acfm)	(scfm)	Vacuum (in-wc)	VOCs by PID (ppmv)	Conc. by Lab (ppmv)	TCE (lb/day)	Total VOCs (lb/day)	TCE (lbs)	Total VOCs (lbs)	Notes

#### NOTES:

TCE = trichloroethene

acfm = actual cubic feet per minute

"F = degrees Fahrenheit

hrs = hours

in-wc = inches of water column

lb/day = pounds per day

lbs = pounds

PID = photoionization detector

ppmv = parts per million by volume

scfm = standard cubic feet per minute

tr = trace (concentration detected at less than reporting limit)

VOCs = volatile organic compounds

- = no measurement

< = not detected at indicated method detection limit</p>

- 1. PID calibrated with 100 ppmv of isobutylene.
- 2. Laboratory analyses were performed by Performance Analytical, Inc. in Simi Valley, California using EPA Method TO-14A.
- 3. Well VMP-1 was first used as an extraction well on 8 March 2001.
- 4. Extraction well VMP-1 is screened in the shallow vadose zone from 19 to 25 feet below ground surface.

#### TABLE 5

### Field Data for Soil Vapor Monitoring Probes

Quarterly Progress Report for January through March 2001

Jervis B. Webb Company of California, 5030 Firestone Boulevard, South Gate, California

	٧N	NP-1	VN	1P-2	VM	P-D1	VMP-D2		
Date	Vacuum	Total VOCs	Vacuum	Total VOCs	Vacuum	Total VOCs	Vacuum	Total VOCs	
		by PID (1,2)		by PID (1,2)		by PID (1,3)		by PID (1,3)	
	(in-wc)	(ppmv)	(in-wc)	(ppmv)	(in-w¢)	(ppmv)	(in-wc)	(ppmv)	
3/16/00	-	68	) Made	150	-	530	MR.	71	
3/17/00	1.8	-	1.0	-	4.7	*	5.2	•	
3/18/00	1.3	-	1.1	-	6.6	~	6.0	•	
3/19/00	1.1		0.7	- [	2.2	-	2.4	-	
3/20/00	2.1	_	1.4	-	2.6	-	3.5	<del></del>	
3/21/00	2.4	-	2.2	-	5.4	-	6.8		
3/22/00	2.6	-	2.3	-	5.8	-	4.5	100 II	
3/30/00	1.8		1.8	•	15	-	16		
4/6/00	2.8	6.4	4.2	7.4	23	3.5	24	150	
4/13/00	4.0	8.2	2.5	6.2	21	23	22	27	
5/11/00	4.5	-	4.0	-	19	-	16	-	
5/18/00	3.2	-	3.4	-	17		18	MAN .	
3/16/00	3.8	-	2.7	-	21	-	22		
7/6/00	-	0.0	-	2.6	•	_	-	-	
7/13/00	2.6	-	1.9	-	m	-		-	
7/20/00	2.9	-	2.1	-	-	- Andrews	-	***	
7/27/00	2.6	*	1.9	•••	*				
9/14/00	5.2	0.5	2.4	0.7	-	-	-	iner	
9/28/00	-	1.3	_	2.4		AAAAAAAAAAAAA	-		
10/26/00	11.5	13.2	11.5	2.2	<b>38</b>	-	-	•	
12/14/00	7.3	-	0.6			-	-	<b>₩</b>	
1/4/01	-	0.9	*	0.4	»-	-	***	-	

#### NOTES:

in-wc = inches of water column


PID = photoionization detector

ppmv = parts per million by volume

VOCs = volatile organic compounds

- = no measurement

- 1. PID calibrated with 100 ppmy of isobutylene.
- 2. Each shallow vapor monitoring probe was purged of approximately 5 to 7 cubic feet of vapor and then sampled and analyzed using a PID.
- 3. Each deep vapor monitoring probe was purged of approximately 50 to 65 cubic feet of vapor and then sampled and analyzed using a PID.
- 4. On days for which two vacuum and PID readings are provided, the values indicate initial and final readings during the site visit.
- 5. Probes VMP-D1 and VMP-D2 have been used as extraction wells since 6 July 2000. For data collected at wells VMP-D1 and VMP-D2, see Tables 4f and 4g, respectively.
- 6. Probe VMP-1 has been used as an extraction well since 8 March 2001 (see Table 4h).
- 7. Soil vapor monitoring probes VMP-1 and VMP-2 are screened in the shallow vadose zone from approximately 19 to 25 feet beneath the ground surface.
- 8. Soil vapor monitoring probes VMP-D1 and VMP-D2 are screened in the deep vadose zone from approximately 30 to 40 and 31 to 41 feet beneath the ground surface, respectively.






0 2,000 4,000
(Approximate Scale in Feet)

Erler & Kalinowski, inc.

Site Location Map

Source: U.S.G.S 7.5 Minute Series "South Gate" Quadrangle, 1964, photorevised 1981.

Jervis B. Webb Company of California South Gate, California April 2001 EKI 991103.01



#### **LEGEND**



Groundwater Monitoring Well

--- Property Line/Site Boundary

# Erler & Kalinowski, Inc.


Groundwater Monitoring Well Locations

Jervis B. Webb Company of California South Gate, California April 2001 EKI 991103.01

Figure 2

#### Notes:

1. All locations are approximate.




#### Notes:

1. All locations are approximate.

2. NR = Not Recorded

Jervis B. Webb Company of California South Gate, California April 2001 EKI 991103.01



62.0 Contour Representing the Elevation of the Groundwater Table in Feet Above Mean Sea Level (msl)

MW-3 Groundwater Monitoring Well (60.34) with Groundwater Elevation (msl)

Property Line/Site Boundary


#### Notes:

- 1. All locations are approximate.
- 2. NR = Not Recorded

# Erler & Kalinowski, Inc.

Elevation of the Groundwater Table on 22 February 2001

Jervis B. Webb Company of California South Gate, California April 2001 EKI 991103.01



Contour Representing the Elevation of the Groundwater Table in Feet Above Mean Sea Level (msl)

⊾WW-3 (60.66)

Groundwater Monitoring Well with Groundwater Elevation (msl)

Property Line/Site Boundary


#### Notes:

- 1. All locations are approximate.
- 2. NR = Not Recorded

# Erler & Kalinowski,

Elevation of the Groundwater Table on 8 March 2001

Jervis B. Webb Company of California South Gate, California April 2001 EKI 991103.01



#### **LEGEND**

Isoconcentration Contour for .1,000-Trichloroethene (Micrograms per Liter)

Groundwater Monitoring Well

Property Line/Site Boundary

#### Notes:


- 1. All locations are approximate.
- 2. Concentrations shown in units of micrograms per liter.

#### Erler & Kalinowski, Inc.

Concentrations of Trichloroethene Detected in Groundwater Samples

Jervis B. Webb Company of California South Gate, California

April 2001 EKI 991103.01




#### Notes:

- 1. All locations are approximate.
- 2. SVE = Soil Vapor Extraction

Jervis B. Webb Company of California South Gate, California


April 2001 EKI 991103.01



# FIGURE 9a Concentrations of Total VOCs versus Time: Blower Influent

Quarterly Progress Report for January through March 2001

Jervis B. Webb Company of California, 5030 Firestone Boulevard, South Gate, California




EKI 991103.01 2001-Q1 Table 4 & Figure 9

#### FIGURE 9b

# Total Concentrations of VOCs versus Time: Extraction Well SVE-1

Quarterly Progress Report for January through March 2001

Jervis B. Webb Company of California, 5030 Firestone Boulevard, South Gate, California




### FIGURE 9c

## Concentrations of Total VOCs versus Time: Extraction Well SVE-2

Quarterly Progress Report for January through March 2001

Jervis B. Webb Company of California, 5030 Firestone Boulevard, South Gate, California




#### FIGURE 9d

# Concentrations of Total VOCs versus Time: Extraction Well \$VE-3

Quarterly Progress Report for January through March 2001

Jervis B. Webb Company of California, 5030 Firestone Boulevard, South Gate, California




EKI 991103.01 2001-Q1 Table 4 & Figure 9

# FIGURE 9e

## Concentrations of Total VOCs versus Time: Extraction Well SVE-D1

Quarterly Progress Report for January through March 2001

Jervis B. Webb Company of California, 5030 Firestone Boulevard, South Gate, California




EKI 991103.01 2001-Q1 Table 4 & Figure 9

#### FIGURE 9f

# Concentrations of Total VOCs versus Time: Extraction Well VMP-D1

Quarterly Progress Report for January through March 2001

Jervis B. Webb Company of California, 5030 Firestone Boulevard, South Gate, California




EKi 991103.01 2001-Q1 Table 4 & Figure 9

# FIGURE 9g Concentrations of Total VOCs versus Time: Extraction Well VMP-D2

Quarterly Progress Report for January through March 2001

Jervis B. Webb Company of California, 5030 Firestone Boulevard, South Gate, California




EKi 991103.01 2001-Q1 Table 4 & Figure 9

### FIGURE 9h

# Concentrations of Total VOCs versus Time: Extraction Well VMP-1

Quarteriy Progress Report for January through March 2001

Jervis B. Webb Company of California, 5030 Firestone Boulevard, South Gate, California



EKi 991103.01 2001-Q1 Table 4 & Figure 9

### APPENDIX A

Groundwater Purge and Water Quality Monitoring Forms for Groundwater Sampling

PROJECT NAME: WLAB		***************************************	***************************************			D.	ATE: غ	3/8/0		
PROJECT NUMBER: 99/10	3.01	WELL	NUMBER:	m	w :	/ PI	ERSONNE	L: 5.6	H	
WELL VOLUME CALCULATION	**************************************					/				
Depth of Depth t	ö		Water			Multiplier				Casing Vo
VVeil (fl.) Water (	<b>f</b> t.)		Column (	fl.)		(below)				(gallons
69.98 - 45	.09				Ħ		w-m*			76.
Mult. for casing diam. = 2-in.=0.16; 4-in.=		6-in.=1.44	gals/fl.							
		······	***************************************		INST	RUMENT	CALIBRA	TION		
No, of bailers prior to start of purg	je: O						Fiel	Ė		Standard
					Instru	ment	mea	sure		measure
PURGE METHOD: 2 11 610	end Fis					<del></del>				
					Condu	costa iltro				
PURGE DEPTH: 65/					1					)
PURGE DEPTH. Ø >		· · · · · · · · · · · · · · · · · · ·			рH	/	511	mu	- 4	1
111111					βH	<b>}</b> ~	and delivery and the second	•		
START TIME: 14:45	END TIN	1E: 15.	//		Turbid	ity				
					Tempe	eralure				
TOTAL GALLONS PURGED:					Depth	Probe				
Time										
Volume Purged (gaillons)	14.50	14:55	14.58	15	03	15.07	15.11			*
volume raiged (galions)	10	20	30	de	'n	45	511	Books and a second		
Temperature (degrees F or C)			<del></del>	<u> </u>	<del></del>	1	<del> </del>	- The second sec		V - MANUT - MANUAL CONTROL OF THE PARTY - MANUAL CONTROL OF THE PA
, , , ,	72.1	71.2	70.1	70	7.2	69.7	69.7	7) (Yn decallableste		
pH (units)				1			ł		一	
	7.67	7.52	7.42	7.	25	7.33	7.29	***************************************		
Specific Conductivity (uS/cm)	0 - 0 -		0 000	4	•4 ~ 4	- 75	- e	1		
Turbidity/Color (NTU)	2.000	1.110	8.890	9.5	121	2.700	5.810	<u> </u>		
(Tray	13.0	4.93	2.91	1	79	1.85	1,40	And the second	ı	*horatotatotato
Odor		<i></i>		<u> </u>	***************************************		<del></del>			ji s
	NOAY	Specialization -								
Depth to Water (ft below TOC)									ŧ	
turing purge Number of Casing			***************************************		······		,			
/olumes removed										
Purge Rate (gallons/minute)		5.1.1.1.5.5.1.1.1.1.1.1.1.1.1.1.1.1.1.1								
	_									1
OMMENTS/ Field i.D.	Time Collecte		Containers	& Pres	servatio	<u>n</u>	Analyses Re	equested	,	
SAMPLES: MOUI		i	2 x 40	mc.	Voi	O WINCE	(82 (701A) HIV	260		1
		/	KION	39 2	Huz	n	182	60		
		•		-	, ,-,	^ \	(Total	1 Chi	MX	1
						1	ענע ו	16101	70	
						`	, 77 ° F	U 9/14 "		-
										1
•			•							
										1

PROJECT NAME: MEAR						DATE: 3,	18/01	
PROJECT NUMBER: 9911	23.01	WELL !	NUMBER:	m	12- 3	PERSONNE	L 501	<del>-4</del>
WELL VOLUME CALCULÁTION		***************************************		<u> </u>			MAKKANAMAKASA UPPI-SUPPI-SUPPI-SUMMAKAN	MANAGOMANIA MANAGOMANIA MANAGOMANIA MANAGOMANIA MANAGOMANIA MANAGOMANIA MANAGOMANIA MANAGOMANIA MANAGOMANIA MA
Depth of Depth to			Water	*	Multip	lier		Casing Vo
Well (ft.) 69.55 Water (f	t) <i>43-25</i>	<b>ć</b> "	Column (I	ft.)	(below	·)		(gallon:
- Mult. for casing diam. = 2-in.≠0.16; 4-in.=0	, –	<del></del>	jals/ft.	ره ري د	0.6	4 = 16	.8	50.4
	***************************************		,,,,	11	STRUME	NT CALIBRA	лоп	<del></del>
No. of bailers prior to start of purg	e: <del>-(-)</del>					Fiek	Ė	Standar
				[ <u>In</u> :	strument	mea	znie	measur
PURGE METHOD: 2 16	and Fo	٠ ج						
	•			Co	inductivity			
PURGE DEPTH: 65				ρH	l	grangement and the second sections of		
		*Management		ρН	l	500	mw.	- 9
START TIME: 10.27	END TIN	ΛE:		Tui	rbidity		Janes	
				Te	mperature			
TOTAL GALLONS PURGED:				De	oth Probe			
Time		A PROGRAMMA AND AND AND AND AND AND AND AND AND AN		'				
	10:34	10:43	10:51	10:5	8 11:0	1 11:10	11:15	11:26
Volume Purged (gallons)	10	20	25	200	35	440	45	٠
ì emperature (degree <b>र ) or</b> C)	//	20	ر می	30	33	40	75	50
(20)	69.7	71.3	72.0	71.5	5 71.7	71.3	72.1	71.9
pH (units)	***************************************			<b>†</b>				***************************************
	7.25	7.29	7.24	7. 2	3 7.3	0 7.09	7.31	7.23
Specific Conductivity (uS/cm)	2360	2 16A	2 - 1.	ر ـ ر ج ا	1266	03.620	2681	Z 241A
Turbidity/Color (NTU)	1					¥ ¥ 1		
	166	118	222	516	347	164	62.5	34.0
Odor				Souther m (2 )				
Depth to Water (ft below TOC)	NONC		Week State of					
during purge	T-S-H-H-H-H-H-H-H-H-H-H-H-H-H-H-H-H-H-H-			l	AND THE PERSON OF THE PERSON O	***************************************		
Number of Casing			**************************************					
/olumes removed		energy special	magamaga aya agamaga					*
Purge Rate (gallons/minute)	1.5		<del></del>	<del>(All Milliong Ji</del> h			company of	
COMMENTS/ Field t.D.	Time Collecte	<u>d</u>	Containers (	& Preserv	ation	Aлаlyses Re	guested	
SAMPLES: MW-2		4	x 40 %	DL V	OPi	8260	2	Ì
			10 / NC 1					
•		9						The second secon
		ر کر. د	mL					
								GENERAL STATEMENT
e.								W construction of the state of
-								
								HHR

# GROUNDWATER PURGE AND WATER QUALITY MONITORING FORM

PROJECT NAME:	WYAA					***************************************		DATE:		9/01	The second secon
1	•	1 de 1 de 1	180011	ww.	_	_			-		
PROJECT NUMBE	K. 941/0.	3.01	VYELL	NUMBER:	11.	<u> 2117 -</u>	2	PERSO	NNEL:	· >. + #	
Depth of	Depth to			Water			Markin	lin v			
Weil (ft.)	Water (ft.)			Column (i			Multip (below				Casing Vo
	***************************************		nive.		ω,		(0001014	•			(gallons
Mult, for casing diam, =	- 2.in =0 16: 4.in =0 5/	di Siin ed Oo		eral - Mi				- Carrier	i		
Mot. (of Casing Grant, ~	2-81,-0. 10, 4-81,-0.0	4, V-110 1.02,	. C-!![!;4-4	A 413×11′	<u>50200000</u>	INCT	DI INTE	LIT A I I		1.7% b. b	
Al Allega agia a		ير				ויפחון	KUME	NT CALI	BRAII	ION	
No. of bailers prior t	o start of purge:	$\Theta$							Field		Standard
PURGE METHOD:	211 61	ounce	1.			Instrum	<u>ient</u>		measu	<u>re</u>	measure
	_					Conduc	tivity				
PURGE DEPTH:	65					pН					
			v8.489			pH		54	£ £	mw.	4)
START TIME:		END TIM	ΛΕ: //·	55		Turbidit	v				
			•			Temper	•				
TOTAL GALLONS F	PURGED:					Depth F					
Time	——————————————————————————————————————	1	L		İ	Осрин	100€				***************************************
		11:32	11:39	11.48	<i>j</i> .	1.55					
Volume Purged (gall	ons)		ĺ		T				Ì		
	·Fr	55	60	70	8	0					
Temperature (degree	eathor (c)	,,	12/ /	710	-	2 2					
pri (units)	PROCESSOR SECTION SECT	1//-/	<b> </b>	71.8	1						
pr. (mo)		7.08	7.20	7.01	7	20					
Specific Conductivity	(uS/cm)	<u> </u>		1	• •	00	***************************************				
	ŧ	3.890	3.830	3.600	3.	73					
Turbidity/Color (NTC	))		AND STATE OF THE S								
		22.5	26.5	10.26	3	.75					
Odor		47.				_				THE PERSON NAMED IN	
Depth to Water (ft be	low TOC)	NONY									
during purge	,					-				POLICE CONTRACTOR OF THE PROPERTY OF THE PROPE	
Number of Casing					••••						
/olumes removed								1			•
<sup>2</sup> urge Rate (gallons/r	ninute)	1.5						· ·		* ormal con normal	1000000 PM
COMMENTS/ Fie	:1:5										<b>инименто</b> постатопостатопостато
		ime Collecte	<u> </u>	Containers &	s Pre	servation		<u>Analys</u>	es Kequ	lested	NOSCH 11 11 11 11 11 11 11 11 11 11 11 11 11
SAMPLES: , m,	ツ-2										***************************************
							-				j
	•										
		•									

PROJECT NAME: NUIDO						D/	ATE: 3/2	8/0/	~"	***************************************
PROJECT NUMBER: 99110.	3	WELL N	NUMBER;	ו ממ	w:	<i>3</i> PE	ERSONNEL	: 5.0	H	
WELL VOLUME CALCULATION:		***************************************			***************************************		***************************************	***************************************	444	·
Depth of Depth to			Water	-		Multiplier			C.	asing Vo
Well (fl.) Water (fl.)			Column (f			(below)				(gallons
69.93 - 45	-21	***	24.7	£.	*	014	= 15	82	v 2	· 47.
Mult. for casing diam, = 2-in,=0.16; 4-in.=0.1			gals/ft.			0,0-7	/ 4	· ¥ V·	N 50	- 7
					INST	RUMENT	CALIBRA	ПОЙ	A0000	****
No, of bailers prior to start of purge:	4						Field			Slandaro
•					Instrun	nent	meas	II F &		
PURGE METHOD: 2"6"	ad En					73400000	**************************************	4:0		measure
TOROL MEINOD.	J. W. 1				C 4					
PURGE DEPTH: 65					Condu	CINTY				
PURGE DEPTH: 60 3					рН			*****	***************************************	1
					ρН		512	mu	1-4	
START TIME: 12.38	END TIM	1E: 13	:01		Turbidi	ty	id	Andrew Control of the		
					Tempe	rature				
TOTAL GALLONS PURGED:					Oepth R	<sup>7</sup> robe				
Time				T						***************************************
	12:41	13:46	12.49	1/2	· 53	12:57	13:81			
Volume Purged (gallons)	10	20		ادم ا	_	-	اسدا			
Temperature (degreeg For C)	10	00	30	71	7	( ) ()	55			
remperature (degrees por 0)	100	1001	140	ي سر ا	er ET	100	684		- SARAGE COLOR	
pH (units)		•	1	ł			1 1	***************************************		
•	7.11	7.36	7.36	7.	43	7.39	7.39			
Specific Conauctivity (uS/cm)		ļ ,	l				<u> </u>		*****	O ANNEXAMENTAL PROPERTY OF THE
	1.620	2.440	3.080	£3. i	300	5.250	2.940			ANALAMONDARAMONDAMON
Turbidity/Color (NTU)				,	, ,	<b>37</b> 1327	-9			
Jaor	45.1	119.0	17.6		7/	3.04	2.10	***************************************		
ogo										
Depth to Water (ft below TOC)	WONA						]	несо <b>ский несоский населений</b>		
during purge									A. A. A. A. A. A. A. A. A. A. A. A. A. A	
Number of Casing				***********				***************************************		
/olumes removed								***************************************	*	
durge Rate (gallons/minute)										!
5011151170	4.0									
COMMENTS/ Field I.D.	Time Collecte	_	Containers &			_	Analyses Rec			***
SAMPLES: M.3			-			-	ver 83			11111111111111111111111111111111111111
		,	1 × 100	m	ı 🕏			41 Ch		***************************************
tan							Hex	r Ph.	ORIN	
mw-3										-
Rinsafe		מ	x 40 p	الو ييس	Vo al		836	. 73		1
RINSATE			•			or a	-			W. Committee
KIN DAFE		/ x	100 19	rep	VLR3f	16	TOTAL	Chio	مهد ميليم	
							Hex	Phlon	2711	

PROJECT NAME: WILLE 3/8/01 DATE: PROJECT NUMBER: 99 1/03.0/ WELL VOLUME CALCULATION: WELL NUMBER: M. W. 4 PERSONNEL: 5, 4 Water Multiplier Depth of Depth to Casing Vot Water (R.) 45 6 Q Well (R.) 4562 Column (ft.) (below) (galigns) 23.44 . 0.64 = 15.0 x33 Mult. for casing diam. = 2-in.=0.16; 4-in.=0.64; 5-in.=1.02; 6-in.=1.44 gals/ft. INSTRUMENT CALIBRATION No. of bailers prior to start of purge: -Field Standard Instrument measura measure PURGEMETHOD: 2 "GRUNDED 3" 1000 Conductivity 1000 PURGE DEPTH: 65 1 6.99 7.00 ρН 2,98 4.01 рΗ END TIME: 09.33 START TIME: 09:30 Turbidity Temperature TOTAL GALLONS PURGED: 55 Depth Probe Time 9.45 8:47 19:39 9.49 9.51 Volume Purged (gallons) 2010 20 30 40 Temperature (degrees F or C) 697 67.6 69.7 69.8 70.0 pH (units) 7.02 6.99 17.04 7.07 7.06 Specific Conductivity (uS/cm) 3 888 4.510 4.580 4.640 4.660 Turbidity/Color (NTU) 15.1 6.20 2.56 2.91 0.76 Odor WONY Depth to Water (It below TOC) during purge Number of Casing Volumes removed Purge Rate (gallons/minute) 4.0 COMMENTS/ Field I.D. Time Collected Containers & Preservation Analyses Requested 2 x 40 ML VAA SAMPLES: MW-4 9:58 HNO:

PROJECT NAME: ALOR	***************************************					DA	ATE: 37/	8/01	
PROJECT NUMBER: 4911	03.01	WELL	NUMBER:	m	W -	5 PE	RSONNE	-5c4	
WELL VOLUME CALCULATION									
Depth of Depth	lo	v.	Water	-		Multiplier			Casing Vol
Well (ft.) Water	(n.) 45.93	<b>L</b>	Column (:	. •		(below)			(gallons)
68.83		-	22.0	7					3= 43.
Mult, for casing diarn. = 2-in.=0.15; 4-in.=			gals/ft.		•	0.64		9-6 ×	3= 43.
ADD A ADD A		***************************************		***************************************	INST	RUMENT	CALIBRA	TION	
No, of bailers prior to start of pur	ge: \varTheta						Field		Standard
PURGE METHOD: 🖰 🔏	2161VN	dF05			lastrun	<u>nent</u>	meas	ure	measure
1 1 1 1					Condu	ctivity			
PURGE DEPTH; \$ 64'					рН	17	st M		
					pH	2	4 3 ///	00-4	
START TIME: 13:45	END TIM	ME: 14.	19		Turbidi	tv			
		• •			Tempe	ratura			
TOTAL GALLONS PURGED:					,				
Time			*	<del></del>	Depth f	71008	T		
inte	12.00	13.59			1 . a. l.	14.14	111.00		
Volume Purged (gallons)				1		1	]	<u> </u>	-
(3,	10	20	30	4	o	50	55		
Temperature (degrees F or C)				<b>_</b>	_	<u> </u>			1
	68.1	69.5	69.9	1.9	8.7	69.5	69.6	Manager in the control of	
pH (units)							· · · · ·		
	6.99	7.18	7.20	7.	20	7.24	7.18		
Specific Conductivity (uS/cm)			Ì	1					
	4.330	4.890	5.043	5.	090	4.970	5.040		
Turbiaity/Color (NTU)			<u> </u>						
	9.10	5.43	2.17	/,	/7	1.45	1130		
Odor		_							
Depth to Water (ff below TOC)	WONE	**************************************							
during purge									
Number of Casing	and the second of the second o		-H0044	wassaa		***************************************			
/olumes removed					A. A.				
Purge Rate (gallons/minute)					-	v .			*
	4.0	-Person.	-		***		Andrews.		
COMMENTS/ Field I.D.	Time Collecte	d	Containers	& Pres	ervatio	n	Analyses Re	guested	***************************************
	***************************************		P				3	distribute.	
SAMPLES: M. 1.5									
						r			
,									
•									

## APPENDIX B

Laboratory Reports and Chain-of-Custody Forms for Groundwater Sampling

### ORANGE COAST ANALYTICAL, INC.



3002 Dow, Suite 532, Tustin, CA 92780 (714) 832-0064 Fax (714) 832-0067 4620 E. Elwood, Suite 4, Phoenix, AZ 85040 (480) 736-0960 Fax (480) 736-0970

# RECEIVED

#### LABORATORY REPORT FORM

MAR 2 6 2001

ERLER & KALINOWSKI, INC. SANTA MONICA OFFICE

Laboratory Name: ORANGE COAST ANALYTICAL, INC.

Address:

3002 Dow Suite 532 Tustin, CA 92780

Telephone:

(714) 832-0064

Laboratory Certification

(ELAP) No.:

1416

**Expiration Date:** 

2003

Laboratory Director's Name (Print):

Mark Noorani

Mark norsam

Client:

Erler & Kalinowski, Inc.

Project No.:

991103.01

Project Name:

Webb

Laboratory Reference: EKI 12211

Analytical Method: EPA 8260 Cam Metals

Date Sampled:

03/08/01

Date Received:

03/08/01

Date Reported:

03/15/01

Sample Matrix:

Water

Chain of Custody Received:

Laboratory Director's Signature:

Client Project ID: Webb Erler & Kalinowski, Inc. ATTN: Mr. Brian Auchard Client Project #: 991103.01

3250 Ocean Park Blvd. Suite 385 Sampled: 03/08/01 03/08/01 Santa Monica, CA 90405 Received: ---03/08/01 03/08/01

SAMPLE DESCRIPTION (Water) Analyzed: 03/13/01 03/14/01 03/15/01 03/15/01 Reported: Laboratory Reference #: EKI 12211 03/15/01 03/15/01 03/15/01 03/15/01 Lab Sample I.D. MB03013 01030150 01030151 01030152 VOLATILE ORGANICS BY GC/MS (EPA 8260) Client Sample I.D. MW-1 MW-2 MW-2 Dup

03/08/01

03/08/01

AOTALITE OVOVINCO DI	GOMB (FLV)	orog chem ou	mpie i.b.		10148-1	INIAAT	MAR-Z Dab
		DILUTION	<b>FACTOR</b>	1.0	200	20	20
ANALYTE	CAS	DETECTION	MDL		SAMPLE	RESULTS	
	NUMBER	LIMIT					
		μg/l		μg/l	μg/l	μg/l	μg/l
Acetone	67-64-1	2.0	2.0	<2.0	<400	<40	<40
3enzen <b>e</b>	71-43-2	0.5	0.5	<0.5	<100	<10	<10
3romodichloromethane	75-27-4	0.5	0.5	<0.5	<100	<10	<10
Bromoform	75-25-2	0.5	0.5	<0.5	<100	<10	<10
Bromomethane	74-83-9	1.0	1.0	<1.0	<200	<20	<20
2-Butanone	78-93-3	1.0	1.0	<1.0	<200	<20	<20
Carbon Disulfide	75-15-0	0.5	0.5	<0.5	<100	<10	<10
Carbon tetrachloride	56-23-5	0.5	0.5	<0.5	<100	<10	<10
Chlorobenzene	108-90-7	0.5	0.5	<0.5	<sup>`</sup> <100	<10	<10
Chlorodibromomethane	124-48-1	0.5	0.5	<0.5	<100	<10	<10
Chloroethane	75-00-3	0.5	0.5	<0.5	<100	<10	<10
2-Chloroethyl vinyl ether	110-75-8	1.0	1.0	<1.0	<200	<20	<20
Chloroform	67-66-3	0.5	0.5	<0.5	<100	<10	<10
Chloromethane	74-87-3	0.5	0.5	<0.5	<100	<10	<10
1,1-Dichloroethane	75-34-3	0.5	0.5	<0.5	<100	<10	<10
1,2-Dichloroethane	107-06-2	0.5	0.5	<0.5	<100	<10	<10
1,1-Dichloroethene	75-35-4	0.5	0.5	<0.5	<100	<10	<10
cis-1,2-Dichloroethene	156-59-2	0.5	0.5	<0.5	<100	44	42
rans-1,2-Dichloroethene	156-60-5	0.5	0.5	<0.5	<100	<10	<10
1,2-Dichloropropane	78-87-5	0.5	0,5	<0.5	<100	<10	<10
cis-1,3-Dichloropropene	10061-01-5	0.5	0.5	<0.5	<100	<10	<10
rans-1,3-Dichloropropene	10061-02-6	0.5	0.5	<0.5	<100	<10	<10
Ethylbenzene	100-41-4	0.5	0.5	<0.5	<100	<10	<10
2-Hexanone	591-78-6	1.0	1.0	<1.0	<200	<20	<20
Viethylene chloride	75-09-2	2.5	2.5	<2.5	<500	<50	<50
4-Methyl-2-pentanone	108-10-1	1.0	1.0	<1.0	<200	<20	<20
Styrene	100-42-5	0.5	0.5	<0.5	<100	<10	<10
1,1,2,2-Tetrachloroethane	79-34-5	0.5	0.5	<0.5	<100	<10	<10
Tetrachloroethene	127-18-4	0.5	0.5	<0.5	<100	<10	<10
Toluene	108-88-3	0.5	0.5	<0.5	<100	<10	<10
1,1,1-Trichloroethane	71-55-6	0.5	0.5	<0.5	<100	<10	<10
1,1,2-Trichloroethane	79-00-5	0.5	0.5	<0.5	<100	<10	<10
Trichloroethene	79-01-6	0.5	0.5	<0.5	23,000	1,800	1,600
Trichlorofluoromethane	75-69-4	0.5	0.5	<0.5	<100	<10	<10
√inyl acetate	108-05-4	1.0	1.0	<1.0	<200	<20	<20
Vinyl acetate Vinyl chloride	75-01-4	0.5	0.5	<0.5	<100	<10	<10
Total Xylenes	1330-20-7	0.5	0.5	<0.5	<100	<10	<10
Fotal Aylenes		RROGATE REC		.0.0	- 100	. 10	
	30	Dibromofluore		93	91	93	95

Dibromofluoromethane

اNT <u>س.م.</u>

93 91 93 95 88 Toluene-d8 91 92 88 95 94 4-Bromofluorobenzene 88

Orange Coast Analytical, Inc.

Erler & Kalinowski, Inc.				Project ID:	Webb		
ATTN: Mr. Brian Auchard			Clien	t Project #:	991103,01		
3250 Ocean Park Blvd. Suit	e 385						
Santa Monica, CA 90405			Sampled:	03/08/01	03/08/01	03/08/01	03/08/01
			Received:	03/08/01	03/08/01	03/08/01	03/08/01
SAMPLE DESCRIPTION (V	-		Analyzed:	03/15/01	03/14/01	03/13/01	03/14/01
Laboratory Reference #:	EKI 12211		Reported:	03/15/01	03/15/01	03/15/01	03/15/01
		Lab S	Sample I.D.	01030153	01030154	01030155	01030156
VOLATILE ORGANICS BY	/ GC/MS (EPA	8260) Client S	Sample I.D.	MW-3	MW-4	MW-5	Rinsate Blank
	DILUTION FACTOR			20	1.0	50	1.0
ANALYTE	CAS	DETECTION	I MDL		SAMPLE	RESULTS	
	NUMBER	LIMIT					
		μg/l		μg/l	μg/l	μg/l	μg/l
Acetone	67-64-1	2.0	2.0	<40	<2.0	<100	<2.0
Benzene	71-43-2	0.5	0.5	<10	<0.5	<25	<0.5
Bromodichloromethane	75-27-4	0.5	0.5	<10	<0.5	<25	<0.5
Bromoform	75-25-2	0.5	0.5	<10	<0.5	<25	2.3
Bromomethane	74-83-9	1,0	1,0	<20	<1.0	<50	<1.0
2-Butanone	78-93-3	1.0	1.0	<20	<1,0	<50	<1.0
Carbon Disulfide	75-15 <b>-</b> 0	0.5	0.5	<10	<0.5	<25	<0.5
Carbon tetrachloride	56-23-5	0.5	0.5	<10	<0.5	<25	<0.5
Chlorobenzene	108-90-7	0.5	0.5	<10	<0.5	<25	<0.5
Chlorodibromomethane	124-48-1	0.5	0.5	<10	<0.5	<25	<0.5
Chloroethane	75-00-3	0.5	0.5	<10	<0.5	<25	<0.5
2-Chloroethyl vinyl ether	110-75-B	1.0	1.0	<20	<1.0	<50	<1.0
Chloroform	67-66-3	0.5	0.5	<10	<0.5	<25	<0.5
Chloromethane	74-87-3	0.5	0,5	<10	<0.5	<25	<0.5
	75-34-3	0,5 0.5	0.5	<10	<0.5	<25	<0.5
1,1-Dichloroethane	107-0 <b>5-</b> 2	0.5	0.5 0.5	<10	<0.5 <0.5	<25	<0.5 <0.5
1,2-Dichloroethane					<0.5 <0.5	<25	<0.5 <0.5
1,1-Dichloroethene	75-35-4	0.5	0.5	55			
cis-1,2-Dichloroethene	156-59-2	0.5	0.5	200	<0.5	260 25	5.4
trans-1,2-Dichloroethene	156-60-5	0.5	0.5	<10	<0.5	<25	<0,5
1,2-Dichtoropropane	78-87-5	0.5	0.5	<10	<0.5	<25	<0.5
cis-1,3-Dichloropropene	10061-01-5	0.5	0.5	<10	<0.5	<25	<0,5
trans-1,3-Dichloropropene	10061-02-6	0.5	0,5	<10	<0.5	<25	<0.5
Ethylbenzene	100-41-4	0.5	0.5	<10	<0.5	<25	<0.5
2-Hexanone	591-78 <b>-</b> 6	1.0	1.0	<20	<1.0	<50	<1.0
Methylene chloride	75-0 <del>9</del> -2	2.5	2.5	<50	<2.5	<125	<2,5
4-Methyl-2-pentanone	108-10-1	1.0	1.0	<20	<1.0	<50	<1.0
Styrene	100-42-5	0.5	0.5	<10	<0.5	<25	<0.5
1,1,2,2-Tetrachloroethane	79-34-5	0.5	0.5	<10	<0,5	<25	<0.5
Tetrachloroethene	127-18-4	0.5	0,5	<10	<0.5	<25	<0.5
Toluene	108-88-3	0.5	0,5	<10	<0.5	140	<0.5
1,1,1-Trichloroethane	71-55-6	0,5	0.5	<10	<0.5	<25	<0.5
1,1,2-Trichloroethane	79-00-5	0,5	0,5	<10	<0.5	<25	<0.5
Trichloroethene	79-01-6	0.5	0.5	1,700	<0.5	3,600	120
Trichlorofluoromethane	75-69-4	0.5	0.5	<10	<0.5	<25	<0.5
Vinyl acetate	108-05-4	1.0	1.0	<20	<1.0	<50	<1.0
Vinyl chloride	75-01-4	0.5	0.5	<10	<0.5	<25	<0.5
Total Xylenes	1330-20-7	0.5	0.5	<10	<0.5	91	<0.5
*		RROGATE RE	COVERY%				
		Dibromofluo		95	95	109	<del>96</del>
		Toluene-d8		90	91	87	87
		4-Bromofluo	robenzene	91	90	96	90
INIT					Ossoci	Coast Applid	tion! Inc

Orange Coast Analytical, Inc.

Erler & Kalinowski, Inc.			Client Project ID:	Webb
.TTN: Mr. Brian Auchard			Client Project #:	991103.01
250 Ocean Park Blvd. Suit	e 385		•	
Santa Monica, CA 90405			Sampled:	03/08/01
,,,,,,,			Received:	03/08/01
AMPLE DESCRIPTION (V	Vater)	,	Analyzed:	03/15/01
Laboratory Reference #:			Reported:	03/15/01
			ample I.D.	01030157
VOLATILE ORGANICS BY	GC/MS (EPA 8	3260) Client St	ample I.D.	Rinsate water
	•		FACTOR	1
ANALYTE	CAS	DETECTION	MDL	SAMPLE RESULTS
	NUMBER	LIMIT		
		μg/l		μg/l
Acetone	67-64-1	2.0	2.0	<2.0
Benzene	71-43-2	0.5	0,5	<0.5
romodichloromethane	75-27-4	0.5	0.5	<0.5
Bromoform	75-25-2	0,5	0.5	2.9
Bromomethane	74-83-9	1.0	1.0	<1.0
-Butanone	78-93-3	1.0	1.0	<1.0
Carbon Disulfide	75-15-0	0.5	0,5	<0.5
Carbon tetrachloride	56-23-5	0.5	0,5	<0.5
hlorobenzene	108-90-7	0.5	0.5	<0.5
Chlorodibromomethane	124-48-1	0.5	0,5	1.2
Chloroethane	75-00-3	0.5	0,5	<0.5
-Chloroethyl vinyl ether	110-75-8	1.0	1,0	<1.0
:hloroform	67-66-3	0.5	0,5	<0.5
Chloromethane	74-87-3	0.5	0.5	<0.5
,1-Dichloroethane	75-34-3	0.5	0.5	<0.5
,2-Dichloroethane	107-06-2	0.5	0.5	<0.5
1,1-Dichloroethene	7 <b>5-</b> 3 <b>5-4</b>	0.5	0.5	<0.5
ris-1,2-Dichloroethene	156-59-2	0.5	0.5	<0.5
rans-1,2-Dichtoroethene	156-60-5	0.5	0.5	<0.5
1,2-Dichloropropane	78-87-5	0.5	0.5	<0.5
cis-1,3-Dichloropropene	10061-01-5	0.5	0.5	<0.5
rans-1,3-Dichloropropene	10061-02-6	0.5	0.5	<0.5
Ethylbenzene	100-41-4	0.5	0,5	<0.5
2-Hexanone	591-78-6	1.0	1.0	<1.0
Nethylene chloride	75-09-2	2.5	2.5	<2.5
-Methyl-2-pentanone	108-10-1	1.0	1.0	<1.0
Styrene	100-42-5	0.5	0.5	<0.5
1,2,2-Tetrachloroethane	79-34-5	D,5	0.5	<0.5
etrachloroethene	127-18-4	0.5	0,5	<0.5
Toluene	108-88-3	0.5	0.5	<0.5
1,1,1-Trichloroethane	71-55-6	0.5	0.5	<0.5
,1,2-Trichloroethane	79-00-5	0.5	0.5	<0.5 0.7
Frichters (transmitters)	79-01-6	0.5	0.5	
Trichlorofluoromethane	75-69-4	0.5	0.5 1.0	<0.5 <1.0
/inyl acetate	108-05-4	1.0 0.5	1.0	<0.5
√inyl chloride	75-01-4	0.5 0.5	0,5 0.5	<0.5 <0.5
Total Xylenes	1330-20-7	u.a RROGATE REC		<b>₹</b> ∪.∂
	50	RRUGATE REC Dibromofluar		95
		Toluene-d8	nillenidis	80 82
		/ Oluene-us	. h. a. m. m. m. m. m.	90

4-Bromofluorobenzene

INT wise

93

Orange Coast Analytical, Inc.

Erler & Kalinowski, inc.

ATTN: Mr. Brian Auchard

3250 Ocean Park Blvd. Suite 385

Santa Monica, CA 90405

SAMPLE DESCRIPTION (Water)

Laboratory Reference #: EKI 12211

Client Project ID: Webb Client Project #: 991103.01

 Sampled:
 -- 03/08/01
 03/08/01
 03/08/01

 Received:
 -- 03/08/01
 03/08/01
 03/08/01

 Reported:
 03/15/01
 03/15/01
 03/15/01
 03/15/01

 Lab Sample I.D.
 MB
 01030150
 01030151
 01030152

 Client Sample I.D.
 -- MW-1
 MW-2
 MW-2 Dup

CCR METALS							
ANALYTE	DATE	EPA	DETECTION		SAMPLE	RESULTS	
	TESTED	METHOD	LIMIT				
			mg/l	mg/I	mg/l	mg/l	mg/l
Antimony	03/14/01	200.7	0.1	<0.1	<0.1	<0.1	<0.1
Arsenic	03/14/01	200.7	0.1	<0.1	0.24	<0.1	<0.1
Barium	03/14/01	200.7	0,01	<0.01	0.13	0.019	0.019
Beryllium	03/14/01	200.7	. 0.01	<0.01	<0.01	<0.01	< 0.01
Cadmium	03/14/01	200.7	0.01	<0,01	<0.01	<0.01	<0.01
Chromium (VI)	03/09/01	218.4	0.01	<0.01	<0.01	< 0.01	< 0.01
Chromium (Total)	03/14/01	200.7	0,01	<0.01	<0.01	<0.01	< 0.01
Cobalt	03/14/01	200.7	0.01	< 0.01	<0.01	<0.01	<0.01
Copper	03/14/01	200.7	0.01	< 0.01	<0.01	<0.01	< 0.01
Lead	03/14/01	200.7	0.05	< 0.05	< 0.05	< 0.05	< 0.05
Mercury	03/12/01	245.1	0.001	<0.001	< 0.001	<0.001	<0.001
Molybdenum	03/14/01	200.7	0.05	< 0.05	0.47	1.1	1.1
Nickel	03/14/01	200.7	0.01	< 0.01	< 0.01	< 0.01	<0.01
Selenium	03/14/01	200.7	0.1	<0.1	<0.1	<0.1	<0.1
Silver	03/14/01	200.7	0.01	< 0.01	<0.01	< 0.01	<0.01
Thallium	03/14/01	200.7	0.1	<0.1	<0.1	<0.1	<0.1
Vanadium	03/14/01	200.7	0.01	<0.01	< 0.01	<0.01	<0.01
Zinc	03/14/01	200.7	0,01	< 0.01	0.016	0.015	0.014

Erter & Kalinowski, Inc.

ATTN: Mr. Brian Auchard

3250 Ocean Park Blvd. Suite 385

Santa Monica, CA 90405

SAMPLE DESCRIPTION (Water)

Laboratory Reference #: EKI 12211

Client Project ID: Webb Client Project #: 991103.01

Sampled: 03/08/01 Received: 03/08/01 Reported: 03/15/01

03/08/01 03/08/01 03/15/01 03/08/01 03/08/01 03/15/01 03/08/01 03/08/01 03/15/01

Lab Sample I.D. 01030153 01030154 01030155 01030157 Client Sample I.D. MW-3 MW-4 MW-5 Rinsate Water

CCR METALS										
ANALYTE	DATE	EPA	DETECTION		SAMPLE RESULTS					
	TESTED	METHOD	LIMIT							
			mg/l	mg/l	mg/l	mg/l	mg/I			
Antimony	03/14/01	200.7	0.1	<0.1	<0.1	<0.1	<0.1			
Arsenic	03/14/01	200.7	0.1	<0,1	<0.1	0.15	<0.1			
Barium	03/14/01	200.7	0.01	0,15	0.027	0.15	0.090			
Beryllium	03/14/01	200.7	0.01	<0.01	<0,01	<0,01	<0.01			
Cadmium	03/14/01	200.7	0.01	<0.01	<0.01	<0.01	<0.01			
Chromium (VI)	03/09/01	218.4	0.01	<0.01	<0.01	<0.01	<0.01			
				<0.01	<0.01	<0.01	<0.01			
Chromium (Total)	03/14/01	200.7	0.01							
Cobalt	03/14/01	200.7	0.01	<0.01	<0.01	<0.01	<0.01			
Соррег	03/14/01	200.7	0.01	<0,01	< 0.01	<0.01	<0,01			
Lead	03/14/01	200,7	0.05	< 0.05	< 0.05	<0.05	< 0.05			
Mercury	03/12/01	245.1	0.001	<0.001	< 0.001	<0.001	< 0.001			
Molybdenum	03/14/01	200.7	0.05	0.71	<0.05	0.84	< 0.05			
Nickel	03/14/01	200.7	0,01	< 0.01	<0.01	< 0.01	<0.01			
Selenium	03/14/01	200.7	0.1	<0,1	<0.1	<0.1	<0.1			
Silver	03/14/01	200.7	0.01	<0.01	< 0.01	<0.01	< 0.01			
Thallium	03/14/01	200.7	0.1	<0,1	<0.1	<0.1	<0.1			
Vanadium	03/14/01	200.7	0.01	< 0.01	< 0.01	<0.01	<0.01			
Zinc	03/14/01	200.7	0.01	0.012	0.025	0,014	0.059			

### 8260 QA / QC REPORT Reporting Unit: µg/l

### 1. Matrix Spike (MS) / Matrix Spike Duplicate (MSD)

Date Performed: 03/13/01 LAB Sample 1, D.: A01030048 Laboratory Reference: EKI 12211

Analyte	Pil	SP	MS	NSD II	WS	<b>PARSON</b>	RPD	ACP	100
		CONC						, MC	PPD
,1-Dichloroethene	0	20	21	21	105	105	0	61-145	14
Benzene	0.0	20	21	20	105	100	5	76-127	11
richloroethene	8.2	20	27	27	94	94	0	71-120	14
oluene	0.0	20	21	21	105	105	0	76-125	13
Chlorobenzene	0,0	20	22	22	110	110	0	75-130	13

R1 = Result of Laboratory Sample I.D.

SPK CONC = Spiking Concentration (≤5 X PQL); PQL = Practical Quantitation Limit.

MS = Matrix Spike Result

MSD = Matrix Spike Duplicate Result

%MS = Percent Recovery of MS: {(MS-R1)/SP} X 100, %MSD = Percent Recovery of MSD: {(MSD-R1)/SP} X 100.

RPD = Relative Percent Difference: {(MS - MSD)/(MS + MSD)} X 100 X 2

ACP%MS(MSD) = Acceptable Range of Percent.
ACP RPD = Acceptable Relative Percent Difference

### 2. Laboratory Quality Control check sample

Date Performed: 03/14/01

AB Sample 1. D.: 8583,84,85,86,87,88

MALKE	SPK CONC.	RESULTS	SERVICE COVERY	ACRIA
rans-1,2-Dichloroethene	50	52	104	80 -120
1,1,1-Trichloroethane	50	50	100	80 -120
1,2-Dichloroethane	50	49	98	80 -120
Tetrachloroethene	50	49	98	80 -120
Styrene	50	49	98	80 -120

ANALYST: NAHID AMERI

DATE: 03/14/01

#### QA / QC REPORT Reporting Unit: mg/l

#### 1. Matrix Spike (MS) / Matrix Spike Duplicate (MSD)

LAB Sample 1 . D .: 01030151, M01030023 (CrVI), 01030151 (Hg)

Analyte	DATE ANALYZED	R1	SP	MS	MSD	%MS	%MSD	RPD	ACP %MS	ACP RPD
Amtimony	03/14/01	0.0	1.0	1.02	1.06	102	106	4	80-120	15
Arsenic	03/14/01	0.0	1.0	1.15	1.18	115	118	3	80-120	15
Barium	03/14/01	0.019	0.10	0.119	0.120	100	101	1	80-120	15
Beryllium	03/14/01	0.0	0.10	0.0998	0.101	100	101	1	80-120	15
Cadmium	03/14/01	0.0	0.10	0.103	0.103	103	103	0	80-120	15
Chromium	03/14/01	0.0	0.10	0.0934	0.0928	93	93	1	80-120	15
Chromium VI	03/09/01	0.0	0.10	0.0964	0.0976	96	98	1	80-120	15
Cobalt	03/14/01	0.0	0.10	0.0924	0.0935	92	94	1	80-120	15
Copper	03/14/01	0.0	0.10	0.111	0.110	111	110	1	80-120	15
Lead	03/14/01	0.0	1.0	0.944	0.970	94	97	3	80-120	15
Mercury	03/12/01	0.0	0.010	0.00990	0.0103	99	103	4	80-120	15
Molybdenum	03/14/01	1.1	1.0	2.12	2.13	102	103	0	80-119	15
Nickel	03/14/01	0.0	0.50	0.430	0.433	86	87	1	80-120	15
Selenium	03/14/01	0.0	1.0	1.04	1.07	104	107	3	80-120	15
Silver	03/14/01	0.0	1.0	0.997	1.00	100	100	0	80-120	15
Thallium	03/14/01	0.0	1.0	0.901	0.930	90	93	3	80-120	15
Vanadium	03/14/01	0.0	0.50	0.503	0,508	101	102	1	80-120	15
Zinc	03/14/01	0.015	0.10	0,111	0.111	96	96	0	80-120	15

R1 = Result of Laboratory Sample I.D.

SPK CONC = Spiking Concentration (<5 X PQL); PQL = Practical Quantitation Limit.

MS = Matrix Spike Result

MSD = Matrix Spike Duplicate Result

%MS = Percent Recovery of MS: {(MS-R1)/SP} X 100. %MSD = Percent Recovery of MSD: {(MSD-R1)/SP} X 100.

RPD = Relative Percent Difference: ((MS - MSD)/(MS + MSD)) X 100 X 2

ACP%MS(MSD) = Acceptable Range of Percent. ACP RPD = Acceptable Relative Percent Difference

4.46	5	area, de terrelation
ALLET LICETA	79 E 12 1 1977 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	DATE ON GAROA
ANALYST.	nnc i iccarai	1 144 1 2" 11 12 12 11 11
S. 58 35 39% 8 54 3 5	~****** * ***********	w
		0,0,0000,0,00,0000000000000000000000000

## 2. Laboratory Quality Control check sample

LAB Sample 1. D.: 01030152, M01030023 (CrVI), 01030151 (Hg

ANALYTE	Date Analyzed	SPK CONC	RESULTS	WRECOVERY	ACP %
Amtimony	03/14/01	0.50	0.46	92	80 - 120
Arsenic	03/14/01	0.50	0.48	96	80 - 120
Barium	03/14/01	0.50	0.48	96	80 - 120
Beryllium	03/14/01	0.50	0,49	98	80 - 120
Cadmium	03/14/01	0.50	0.49	98	80 - 120
Chromium	03/14/01	0.50	0.49	98	80 - 120
Chromium VI	03/09/01	0.35	0.33	94	80 - 120
Cobalt	03/14/01	0,50	0.51	102	80 - 120
Copper	03/14/01	0.50	0.48	96	80 - 120
Lead	03/14/01	0.50	0.47	94	80 - 120
Mercury	03/12/01	0.0050	0.0047	94	80 - 120
Molybdenum	03/14/01	0.50	0.48	96	80 - 120
Nickel	03/14/01	0.50	0,46	92	80 - 120
Selenium	03/14/01	0.50	0.47	94	80 - 120
Silver	03/14/01	0.50	0.47	94	80 - 120
Thallium	03/14/01	0.50	0.47	94	80 - 120
Vanadium	03/14/01	0.50	0.48	96	80 - 120
Zinc	03/14/01	0.50	0.49	98	80 - 120

Erler & Kalinowski, Inc.

ATTN: Mr. Brian Auchard 3250 Ocean Park Blvd. Suite 385

Santa Monica, CA 90405

Sample Description: Soil,

Laboratory Reference #: EKI 12211

Client Project ID: Webb Client Project #: 991103.01

Sampled:

03/08/01

Received:

03/08/01

Analyzed:

03/20/01

Reported:

03/22/01

### TOTAL ARSENIC (EPA 206.2)

LABORATORY SAMPLE NUMBER	CLIENT SAMPLE NUMBER	SAMPLE RESULTS µg/l
01030150	MW-1	320
01030151	MW-2	6,6
01030152	MW-2 Duplicate	5.6
01030153	MW-3	80
01030154	MW-4	7.9
01020155	MW-5	190
01030157	Rinsate Water	44
Detection Limit		1.0

Analyte reported as N.D. were not present above the stated limit of detection.

#### QC DATA REPORT

Analysis: Arsenic (EPA 206.2)

Date of Analysis: 03/20/01

Laboratory Sample No : 01030157 Laboratory Reference No : EKI 12211

7	Analyte	R1	SP	MS	MSD	PR1	PR2	RPD
		(ppb)	(ppb)	(ppb)	(ppb)	%	%	%
1	Arsenic	2.2	5.0	6.88	7.28	93.6	102	6

#### **Definition of Terms:**

R1 Results Of First Analysis

SP Spike Concentration Added to Sample

MS Matrix Spike Results

MSD Matrix Spike Duplicate Results

PR1 Percent Recovery Of MS: {(MS-R1) / SP) x100

PR2 Percent Recovery Of MSD: {(MSD-R1) / SP) x 100

RPD Relative Percent Difference: {(MS-MSD) / (MS+MSD)) x 100 x 2

# Analysis Request and Chain of custous Record

# ORANGE COAST ANALYTICAL, INC.

3002 Dow, Suite 532 Tustin, CA 92780 (714) 832-0064, Fax (714) 832-0067 4620 E. Elwood, Suite 4 Phoenix, AZ 85040 (480) 736-0960 Fax (480) 736-0970

Lab Job	No:		
Page		of <b>L</b>	į,
			ŧ

REQUIRED TAT

CUSTOMER INFORMATION  COMPANY: Erlec + Kelinowski, Ir	PRO	ECTNAME		Jepp Jepp	FORMATI	ON		Z			//	//	
SEND REPORT TO: Brish Avchad	NUM			51103	5.01					II	//		
ADDRESS: 3250 Ocean tak Blu	<u> </u>	KTION: RESS:	hans, toda		<del> ``</del>		<b>5</b> 1. 1			[ ]	///	[ ]	
Sonto Monice CA 9040				30 F	ρ• <del>/</del> •		<u>31v4.</u>			\display \di			<i>///</i>
PHONE 310-314-8855 FAX 310-314-9	N SAM	PLED BY:	***	<b></b>		•			6/ /	ž/ /		[ ]	
, sample jo		100		SAMPLE THE	SAMPLE PATTE	CONTRACT	PRES.			7 /			REMARKS/PRECAUTIONS
MW-1	2	3 8	9)	1500	W	VOA	HL	X					2 week turneround
7400	2	일일	101	1220				X					
MW-2 duplicate	2	38	10[	195				X					
MW-3	2	<u> </u>	<u>101</u>	1315				X					
MWH	2	38	ارولا	1005				X					
MW-5	2	3/8	lo l	1420				X					
	0	1585	60	$\omega \omega$									
Rinde blank	2	3/9	bil	1325				X					
Rinsate Woter	2	3/	96	1335	4	٧	<u> </u>	8	$\perp$ X				Hold-run for
													Bato if ann
													detections in
													rinsate blank
													(CS)/ EKI pls//
		<u> </u>				I,	_ ~						<u>'</u>
Total No. of Samples:			Metho	od of Shipm	nent: <	<u>طوا،</u>	reces	圡ţ	<u> باواد</u>				
Relinquished By Date/Time:	3/2 16:	/*/	Recei	ved By:	<b>`</b>		Date/Time	"สไ	n n n	Re			it: (check)
Relinquished By: Date/Time:	146		Recei	ved By:		1	Date/Time	):			RVQCB		OTHER
Relinquished By: Date/Time:			Recei	ved For La	b By:		Date/Time		: 52,7	3 3			(check)

# Analysis nequest and Chain or custouy Record

200000	-998889
2000	2000
30000	9999
18888	2000
0.0000000000000000000000000000000000000	96666
3656360	.000000
333333	2800000
.00000000	2000000000
200000000000000000000000000000000000000	9999999999
30000000000	700000000000
300000000000	70000000000
***************************************	~~~
366999999	× 100000000000
2000000000	
~~~~~~~~~	5000 TORRESONS
38388	2723. 1888
233	

ORANGE COAST ANALYTICAL, INC.

3002 Dow, Suite 532 0 0 0 Tustin, CA 92780 0 0 0 0 (714) 832-0064, Fax (714) 832-0067

4620 E. Elwood, Suite 4 Phoenix, AZ 85040

			8.0	99	ю	w	22	×	52	×	w	83	ж.	١.		90		ĸ,	ж,		٠,	88	٠,	ю.	***	ь.			×																						
																																							9												
	83	8	10	×	٠	88		×		8		×	e.		ŭ,		×	×	×	×		×				88	œ.	ø.					2	68	6		33	•	4	00	ĸ.			œ.		12			1	•	
		3.	×	1	и	1		А		8		и.	3	ĸ.	2		×		4.	-3	ĸ.	8		٧.		8			~		ين	60	Ä.	- 7	۲.	С	u				ж	6.7	26		8	7	А.	٤.	ľ	σ.	
	-3	-	ú	×	7	я	•	ě.		80	۲.	4	Э	8	Э	79	٠.	2	12	•	۲.		ι.	3.		88		-	٠,	и,	ĸ.		Ł	44	۲.	63	31	2	33	1	38		13	-2		٠.	ě.	ж.			٧.
	и	ж		×	×	30		м		æ,	α		•			80	ĸ.	×	×	۲.		٠.		90		90	20	97	7	м	90				М,	-	ж.	×	0			•	88	35			9	~	80		

Page of \_\_\_\_\_\_

			ORMATIO)	l .					<b>\$</b> //	
SUITE 385 SANTA MONICA, CA 90405 PHONE:(310)314-8855 FAX:(310)314-8860	Jaumess 5030	FIREST H GATE		BLUD 1 30	,5		<b>\$</b> 5			
SAMPLE 10 CC	ACCE CARPLE	144			-10		RYY	4//		/s/ REMARKS/PRECAUTIONS
MW-1	3/8/61	TE\$S	W	PAL	μ <b>ğ</b> ο.	<b>3</b>	Tx T			
MW-3	380	155	W	واعام	H.		X			
MW 42 - DVD	3 900	1201	<b>3</b> -0 }	<b>L</b> ARE	HMA	М,	l v			
14M33	1 3/8/51	1319	Wi	<u> </u>	High:	<u> Al</u>				
MANA	3/8/61	1088	<i>19</i> 8	<u> </u>	HMO	<u>R</u>	x			de
_MW-5	1 3/8/61	1436	<u>u</u>	Balk	HAD		2			
Kin sate Water	7 78/01	1338	D)	286	PM.	MΚ	<u>l</u>			
	•	0	<i>''</i>	9 .M	93	<b>%</b>				
		2	3 /	- 2	8	<u> </u>	- 3		٥	•
			3	i i	1 [.	Vi.	Š		À	
	× 1		•		Į.)		K			
		n								
u,					-					
	v   %			4 1		Щ.				
Total No. of Samples:		od of Shipme	ent:	0.000.000.000.000.000.000.000	11085					
Relinquished By: Date/Time: 3/2	9/0/ Recu	ived By:	72	<u> </u>	)ate/Time	<u>iZb</u>	<u>j</u> 6/			ormat: (check) S.D. HMMD
Relinquished By: Date/Titge	Hece H-b	nived By:		C	)ate/Time	15	<del>) 14</del>	RW	CB	OTHER
Relinquished By: Date/Time:	Peca プ	oived ForjLat	) By:   Se/	C	ate/Time	<i>!</i>	5 57)	Sampl intac		grity: (check) on ice

## Erler & Kalinowski, Inc.

Consulting Engineers and Scientists

3250 Ocean Park Blvd , Suite 385 Santa Monica, CA 90405 www.ekiconsult.com Tel. (310) 314-8865 Fax (310) 314-8860

1 May 2001

Mr. Michael Farley, Esq. Jervis B. Webb Company 34375 West Twelve Mile Road Farmington Hills, Michigan 48331

Subject:

Quarterly Progress Report for January through March 2001 For the Jervis B. Webb Company of California Property, 5030 Firestone Boulevard, South Gate, California (RWQCB SLIC File No. 744; EKI 991103.01)

Dear Mr. Farley:

Erler & Kalinowski, Inc. is pleased to present the enclosed Quarterly Progress Report for January through March 2001, dated 30 April 2001. This report describes the activities completed during the period from January through March 2000 at the Jervis B. Webb Company of California property located at 5030 Firestone Boulevard in South Gate, California.

Please contact us if you have any comments or questions.

Very truly yours,

ERLER & KALINOWSKI, INC.

Steven R. Chambers, Ph.D.

Project Manager

Steven G. Miller, P.E. Supervising Engineer

ce: Mr. Michael Feeley